


KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX805R

Heavy Duty | Prison units





KWC-No.

2000100953

Version with WC pan angled 45° to the left

2000100954

Version with centrally arranged WC pan Dimensions 390 x 1000 x 780 mm (W x H x D)

2000100955

Version with WC pan angled 45° to the right Dimensions 700 x 1000 x 670 mm (W x H x D)

Chromium nickel steel WC wash basin combination, satin finish surface for installing in front of a utility room accessible from the back with remotely controlled tap components for fitting in the utility room, fixing from the back with threaded pins. Mounting stand, material thickness 2 mm with elevated rear wall including wall outlet and press button operation, seamless welded WC paper comportment and seamless moulded wash basin with trap, outlet DN 40. WC pan, material thickness 1.6 mm with full-length skirting, arranged on the right 45 degrees, bowl rim where nothing can hide,

WC position

middle

right

flushing certified pursuant to EN 997, horizontal outlet at the back DN 100. Self-closing gate valve with remote control to connect to premixed hot water or cold water, closing automatically with no blow back. Condensation water-proof concealed cistem with single flush technology (9 or 6 litres) Including fixing material.

Overall dimensions 700 x 1000 x 670 mm (W x H x D) WC position on the right

Technical Data

Technical Data	
body width	
front access panel	
floor fixing joggle plate	
inlet size	
material	
material code	
material thickness body	
material thickness WC	
outlet size	
overall depth	
overall height	
overall width	
overflow	
pipework material	
self closing push buttons	
toilet roll holder diameter	
shroud design	
soap dish	
spout length	

390 mm	
yes	
no	
DN 15	
stainless steel	
1.4301 Chrome Nickel steel V2A	
2 mm	
1.5 mm	
DN 50 / DN 100	
669 mm	
1,000 mm	
699 mm	
no	
stainless steel	
mechanical	
153 mm	
round shape	
no	
83 mm	





KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX805R Heavy Duty | Prison units

surface finish	satin finished
tap with integrated bubbler	no
type of flushing fitting	WC cistern
type of mounting	bolt mounting
type of toilet seat	no seat
type of WC	floorstanding
upper edge of basin height	850 mm
upstand depth	20 mm
upstand height	150 mm
WC height	400 mm
WC position	right

Spare Parts









Remote operation valve

2000104780 EFLSY0027

Wall outlet, DN 15

2000107291 ZTAPS0004

Functional element

2000105612 EFLSY0036

Remote operation hose

2000104803 EAQLN0019