


KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815L

Heavy Duty | Prison units





KWC-No.

2000100965

Version with WC pan angled 45° to the left

2000100966

Version with centrally arranged WC pan Dimensions $500 \times 1050 \times$ 890 mm (W x H x D)

Version with WC pan angled 45° to the right Dimensions 810 x 1050 x 780 mm (W x H x D)

Chromium nickel steel WC wash basin combination, satin finish surface for installing against a wall, invisible fixing with grub screws, lockable inspection opening. Mounting stand, material thickness 2 mm with elevated rear wall including wall outlet and press button operation, seamless welded toilet paper roll compartment and seamless moulded oval wash basin with plastic trap. WC pan, material thickness 1.6 mm with full-length skirting, arranged on the left 45 degrees, bowl rim where nothing can hide,

WC position

middle right

flushing certified pursuant to EN 997, horizontal outlet at the back DN 100. Self-closing gate valve with remote control to connect to premixed hot water or cold water, closing automatically with no blow back. Condensation water-proof concealed cistern with single flush technology (9 or 6 litres) Including fixing material.

Overall dimensions $810 \times 1050 \times 780$ mm (W x H x D) WC position on the left

Technical Data	
body width	
front access panel	
floor fixing joggle plate	
inlet size	_
material	_
material code	_
material thickness body	
material thickness WC	_
outlet size	_
overall depth	
overall height	
overall width	
overflow	
pipework material	_
self closing push buttons	_
toilet roll holder diameter	
shroud design	
soap dish	
spout length	

500 mm	
yes	
no	
DN 15	
stainless steel	
1.4301 Chrome Nickel steel V2A	
2 mm	
1.5 mm	
DN 50 / DN 100	
780 mm	
1,050 mm	
810 mm	
no	
stainless steel	
mechanical	
153 mm	
round shape	
no	
83 mm	





KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815L Heavy Duty | Prison units

surface finish	satin finished	
tap with integrated bubbler	no	
type of flushing fitting	WC cistern	
type of mounting	wall mounting	
type of toilet seat	no seat	
type of WC	floor standing	
upper edge of basin height	850 mm	
upstand depth	160 mm	
upstand height	200 mm	
WC height	400 mm	
WC position	left	