


KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815M

Heavy Duty | Prison units





WC position

left

middle

right

KWC-No.

2000100965 Version with WC pan angled 45° to the left

2000100966

Version with centrally arranged WC pan Dimensions 500 x 1050 x 890 mm (W x H x D)

2000100967

Version with WC pan angled 45° to the right Dimensions 810 x 1050 x 780 mm (W x H x D)

Chromium nickel steel WC wash basin combination, satin finish surface for installing against a wall, invisible fixing with grub screws, lockable inspection opening. Mounting stand, material thickness 2 mm with elevated rear wall including wall outlet and press button operation, seamless welded toilet paper roll compartment and seamless moulded oval wash basin with plastic trap. WC pan, material thickness 1.6 mm with full-length skirting, arranged in the middle 90 degrees, bowl rim where nothing can hide, flushing certified pursuant to EN 997, horizontal outlet at the back DN 100. Self-closing gate valve with remote control to connect to premixed hot water or cold water, closing automatically with no blow back. Condensation water-proof concealed cistem with single flush technology (9 or 6 litres) Including fixing material.

Overall dimensions 500 x 1050 x 890 mm (W x H x D) WC position in the middle

Technical Data

body width	
front access panel	
floor fixing joggle plate	
inlet size	
material	
material code	
material thickness body	
material thickness WC	
outlet size	
overall depth	
overall height	
overall width	
overflow	
pipework material	
self closing push buttons	
toilet roll holder diameter	
shroud design	
soap dish	
spout length	

yes				
no				
DN 15				
stainless st	eel			
1.4301 Chr	ome Nickel	steel V2A	Ą	
2 mm				
1.5 mm				
DN 50 / DN	100			
890 mm				
1,050 mm				
500 mm				
no				
stainless st	eel			
mechanical				
153 mm				
round shap	e			
no				





KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815M Heavy Duty | Prison units

surface finish	satin finished
tap with integrated bubbler	no
type of flushing fitting	WC cistern
type of mounting	wall mounting
type of toilet seat	no seat
type of WC	floor standing
upper edge of basin height	850 mm
upstand depth	160 mm
upstand height	200 mm
WC height	400 mm
WC position	middle