


KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815R

Heavy Duty | Prison units





KWC-No.

2000100965 Version with WC pan angled 45° to the left

2000100966

Version with centrally arranged WC pan Dimensions 500 x 1050 x 890 mm (W x H x D)

2000100967

Version with WC pan angled 45° to the right Dimensions 810 x 1050 x 780 mm (W x H x D)

Chromium nickel steel WC wash basin combination, satin finish surface for installing against a wall, invisible fixing with grub screws, lockable inspection opening. Mounting stand, material thickness 2 mm with elevated rear wall including wall outlet and press button operation, seamless welded toilet paper roll compartment and seamless moulded oval wash basin with plastic trap. WC pan, material thickness 1.6 mm with full-length skirting, arranged on the right 45 degrees, bowl rim where nothing can hide, flushing certified pursuant to EN 997, horizontal outlet at the back DN 100. Self-closing gate valve with remote control to connect to premixed hot water or cold water, closing automatically with no blow back. Condensation water-proof concealed cistem with single flush technology (9 or 6 litres) Including fixing material.

Overall dimensions 810 x 1050 x 780 mm (W x H x D) WC position on the right

WC position

left

middle

right

Technical Data

body width	
front access panel	
floor fixing joggle plate	
inlet size	
material	
material code	
material thickness body	
material thickness WC	
outlet size	
overall depth	
overall height	
overall width	
overflow	
pipework material	
self closing push buttons	
toilet roll holder diameter	
shroud design	
soap dish	
spout length	

500 mm		
yes		
no		
DN 15		
stainless steel		
1.4301 Chrome	Nickel steel V2A	
2 mm		
1.5 mm		
DN 50 / DN 10)	
780 mm		
1,050 mm		
810 mm		
no		
stainless steel		
mechanical		
153 mm		
angled corners		
no		
83 mm		





KWC HEAVY-DUTY WC washbasin combination

Modell-Linie: HEAVYDUTY | HDTX815R Heavy Duty | Prison units

surface finish	satin finished
tap with integrated bubbler	no
type of flushing fitting	WC cistern
type of mounting	wall mounting
type of toilet seat	no seat
type of WC	floor standing
upper edge of basin height	850 mm
upstand depth	160 mm
upstand height	200 mm
WC height	400 mm
WCposition	right