KWC

KWC AQUALINE
WC flushing valve

Modell-Linie: AQUALINE | AQRM553C
Flushing systems | Self closing wc flushing system


G3/4B
Ø90 □110
16
4
50-60
160
Ø26
102

KWC-No.		**sound insulation**	
2000103712		I-	
2000101061 Version without noise group I		no	

AQUALINE WC flush valve DN 20 with remote control, for vandal resistant
applications, installation of flush valve outside the user room, remote
control in wall installation box with stainless steel cover plate and metal push button.

Technical Data

calculation flow rate cold wat		1 l/s	
Cover plate height		110 mm	
functional principle		hydraulic self-closing	
diameter nominal		DN 20	
material casing		stainless steel	
material code casing		1.4301 Chrome Nickel steel V2A	
material fitting		brass-look	
maximum flow pressure		4 bar	
maximum flushing flow		1.3 l/s	
maximum flush water volume		9 Liter	
minimum flow pressure		1.2 bar	
minimum flushing flow		1 l/s	
minimum flush water volume		6 Liter	
protective shutdown		no	
sound insulation		no	
surface finish casing		satin finished	
surface finish fitting		raw	
type of flushing fitting		WC flush valve	
type of mounting		concealed	
type of operation		manual operation	
water connection		threaded connection (external)	
Basic colour		stainless steel-look	

Spare Parts

Modell-Linie: AQUALINE | AQRM553C
Flushing systems | Self closing wc flushing system

Remote operation valve

2000104780
EFLSY0027

**WC flush valve DN 20**

2000104835
EAQLN0020

Head part

2000104389
EFLSY0005

Outlet screw connection

2000106164
EAQLN0018

Remote operation hose

2000104803
EAQLN0019