

KWC-No.

2000101449

Electronic tap components for washbasin unit, for touch-free control of the water supply

Electronic fitting components for the touch-free control of water for washing unit. Consisting of near-field sensor, electronic module, solenoid valve with shut-off, flush pipe, hose and electric T-junction.

24 V DC

Technical Data

with backflow preventer	no
calculation flow rate cold wat	0.2 l/s
default automatic hygiene flus	24h after the last activity
default flow time	10 Seconds
depressurised	no
with filter	yes
functional principle	electronic self-closing
hygiene flushing	yes
diameter nominal	DN 15
inlet size	G 1/2 A
Locking mechanism	Top section, non-ceramic
minimum flow pressure	1 bar
type of mixing	no
Parameterization	network
Pop-up waste set	no
power supply connection	A3000 open 24 V DC
power consumption	7 Voltampere
Type of power supply	Transformer
protective system IP	IP68 / 44
with rosettes/cover plate	no
protective shutdown	no
sound insulation	no
surface treatment fitting	none
temperature limit	no
thermal disinfection	yes
with transformer/power supply	no

KWC

Electronic tap components

Modell-Linie: PWC_A3000_OPEN | AQUA121

Taps | Electronic taps

type of mounting	concealed
type of operation	sensor operation
type of sensor	capacitive-electronic sensor
type of tap	in-wall tap
volume flow rate at 3 bar	0.5 l/s
water connection	threaded connection (external)
Accent colour	none
Basic colour	Other

Mandatory Accessories



ECC2 function controller

2000108123
ZA3OP0011




Power supply unit

2030068573
ASEX1031



Power supply unit

2000100375
ZAQUA007



System cable

2000104272
ZAQUA011




System cable

2000104274
ZAQUA012



System cable


2000100801
ZAQUA077



System cable

2000100852
ZAQUA078

Spare Parts



Solenoid valve

2000104454
ETAPS0023
