


KWC AQUAFIX

Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002

Installation frames | Installation units urinals





KWC-No.

2000110549

Installation frame for stainless steel urinals with flush valve for inwall installation

AQUAFIX installation frame for stainless steel urinals, with fully assembled basic installation kit for in-wall urinal flush valves, manually operated or touch-free, opto-electronically controlled. Self-supporting, powder-coated, steel frame construction, TÜV tested, for installation of single units in dry-wall lining, adjustable height

fixing as well as tap connection and outlet mount, sound-insulated wall duct with G $1/2,\,$ universal outlet bend DN 50, urinal fixing bolts, building protection and fixing materials.

Dimensions $525 \times 1440 \text{ mm} (W \times H)$

Technical Data

application	urinals
barrier-free	no
Built-in fitting model	Built-in section
height adjustment	200 mm
diameter nominal	DN 15
material	Steel
minimum wall thickness	135 mm
type of mixing	no
outlet size	DN 50
overall depth	135 mm
overall height	1,440 mm
overall width	525 mm
position of power connection	from side
type	installation element
type of mounting	wall and floor mounting

Mandatory Accessories



KWC AQUAFIX

Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002 Installation frames | Installation units urinals



F5E electronic urinal flush valve for inwall installation

2030067743 F5EF3010

Optional Accessories



AQUAFIX wall bracket

2000100867 ZCMPX140

 $\label{lem:KWC Group AG | Home: info@kwc.com| Professional: kwc-export.int@kwc.com | www.kwc.com| \\$