




KWC AQUAFIX
Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002
Installation frames | Installation units urinals



KWC-No.

2000110549

Installation frame for stainless steel urinals with flush valve for in-wall installation

AQUAFIX installation frame for stainless steel urinals, with fully assembled basic installation kit for in-wall urinal flush valves, manually operated or touch-free, opto-electronically controlled. Self-supporting, powder-coated, steel frame construction, TÜV tested, for installation of single units in dry-wall lining, adjustable height

fixing as well as tap connection and outlet mount, sound-insulated wall duct with G 1/2, universal outlet bend DN 50, urinal fixing bolts, building protection and fixing materials.

Dimensions 525 x 1440 mm (W x H)

Technical Data

application
barrier-free
Built-in fitting model
height adjustment
diameter nominal
material
minimum wall thickness
type of mixing
outlet size
overall depth
overall height
overall width
position of power connection
type
type of mounting

urinals
no
Built-in section
200 mm
DN 15
Steel
135 mm
no
DN 50
135 mm
1,440 mm
525 mm
from side
installation element
wall and floor mounting

Mandatory Accessories

KWC AQUAFIX

Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002

Installation frames | Installation units urinals



F5E electronic urinal flush valve for in-wall installation

2030067743

F5EF3010

Optional Accessories



AQUAFIX wall bracket

2000100867

ZCMPX140