


KWC

Emergency shower activated by a pull-rod with water supply from ceiling or from left or right

Modell-Linie: EMERGENCYSHOWERS | FAID0003

Emergency showers | Whole body showers





KWC-No.

2030019025

Pull-rod operated emergency shower, surface mounting near the door, with water supply from ceiling and operation with triangle handle right or water supply from both sides and operation left or right near the exit. Valve with wall bracket and emergency showerhead over the middle of the door. Non-self-closing, the water flow is stopped by pushing up the pull rod, green EPS coating (RAL

6032), complies with EN 15154, Part 1. Includes the "emergency shower" safety symbol on an adhesive label in compliance with ISO 3864, Part 1. Volumetric flow rate approx. 65 l/min at 1 bar pressure, approx. 110 l/min at 3 bar pressure, water connection G 3/4.

Technical Data

colour	
spout projection	
type of connection	
type of fitting	
volume flow rate at 1 bar	
volume flow rate at 3 bar	

reen
ipe connection
odoors
.08 l/s
.83 l/s

Optional Accessories

Extension for coupling-rod

2030061050 ZFAID0003

Spare Parts



KWC

Emergency shower activated by a pull-rod with water supply from ceiling or from left or right

Modell-Linie: EMERGENCYSHO WERS | FAID0003 Emergency showers | Whole body showers





Emergency showerhead

2030018810 FAID0001

Safety label emergency shower

2000101152 FAID904