



## KWC

Emergency shower activated by a pull-rod with water supply from the ceiling or from the right

Modell-Linie: EMERGENCYSHOWERS | FAID0006

Emergency showers | Whole body showers





### KWC-No.

#### 2030019084

Technical Data

Pull-rod operated emergency shower, for surface mounting, with water supply from the ceiling or from the right, valve operated by triangular handle. With wall bracket and emergency shower head. Non-self-closing, the water flow is stopped by pushing up the pull rod, green EPS coating (RAL 6032), complies with EN 15154, Part 1, includes the "emergency shower" safety symbol on an adhesive label in compliance with ISO 3864, Part 1 and user instructions. Volumetric flow rate approx. 65 l/min at 1 bar pressure, approx. 110 l/min at 3 bar pressure, water connection G 3/4.

colour	green	
spout projection		
type of connection	pipe connection	
type of fitting	wall mounted	
volume flow rate at 1 bar	1.08 l/s	
volume flow rate at 3 bar	1.83 l/s	

#### **Optional Accessories**



#### Extension for coupling-rod

2030061050 ZFAID0003

**Spare Parts** 

KWC Group AG | Home: info@kwc.com| Professional: kwc-export.int@kwc.com | www.kwc.com



# кwс

Emergency shower activated by a pull-rod with water supply from the ceiling or from the right

Modell-Linie: EMERGENCYSHOWERS | FAID0006 Emergency showers | Whole body showers





кжс

**2030018810** FAID0001

Safety label emergency shower **2000101152** FAID904