


## KWC F5E

## Electronic pillar tap with battery operation

# Modell-Linie: F5E | F5EV1001 Taps | Electronic taps





#### KWC-No.

#### 2030027922

F5E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, high-polished chromium-plated brass. Anti-theft aerator, design SLIM, with

#### volume flow rate at 3 bar

0.08 l/s

integrated flow regulator 5.0  $\emph{l}$ /min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

### Technical Data

with backflow preventer	
calculation flow rate cold wat	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
number of batteries	
Parameterization	
Pop-up waste set	
power supply connection	
power consumption	
Type of power supply	
protective system IP	
with rosettes/cover plate	
protective shutdown	
sound insulation	
Spout	<del></del>

no	
0.1 l/s	
no	
24h after the last activity	
no	
yes	
electronic self-closing	
yes	
DN 15	
G 3/8	
Top section, non-ceramic	
brass	
1 bar	
no	
1	
remote control	
no	
Battery 6 V	
1.5 Voltampere	
Battery	
IP59K	
no	
yes	
no	
fixed	









## KWC F5E

## Electronic pillar tap with battery operation

# Modell-Linie: F5E | F5EV1001 Taps | Electronic taps

spout projection	125 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	no	
thermal disinfection	no	
with transformer/power supply	no	
type of batteries	CR-P2 Lithium battery 6V	
type of mounting	tap hole	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	pillartap	
volume flow rate at 3 bar	0.08 l/s	
water connection	hose (gland nut)	
Accent colour	none	
Basic colour	chrome-look (glossy)	

#### **Optional Accessories**







Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005

2-button remote control for fittings F3 and F5

**2030036849** ACEX9004

Socket

**2030040334** ACEX1001

Anti-twist protection for F5S

2030035383 ACXX1001







PURETHERM under-table thermostat

2030012758 PURE0031

5.0 l/min aerator, angle-adjustable

2030041326 ACXX1002

3.0 I/min. aerator

2030041424 ASXX1008



## KWC F5E

Electronic pillar tap with battery operation

# Modell-Linie: F5E | F5EV1001 Taps | Electronic taps

## **Spare Parts**





### Solenoid valve cartridge

**2030045522** ACXX9002

## Mounting key

**2030041329** ACXX1003