


## KWC F5E

Electronic pillar tap with plug-in power supply unit

#### Modell-Linie: F5E | F5EV1002

Taps | Electronic taps





#### KWC-No.

2030035330

F5E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve cartridge and sensor in all-metal housing, high-polished chromium-plated brass. Antitheft aerator, design SLIM, with integrated flow regulator 5.0 l/min.

#### volume flow rate at 3 bar

0.08 l/s

Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. With 100 - 240 V AC plug-in power supply unit.

#### Technical Data

with backflow preventer	no
calculation flow rate cold wat	0.1 l/s
compatible A3000 open	no
default automatic hygiene flus	24h afte
depressurised	no
with filter	yes
functional principle	electronic
hygiene flushing	yes
diameter nominal	DN 15
inlet size	G 3/8
Locking mechanism	Top sect
material fitting	brass
minimum flow pressure	1 bar
type of mixing	no
Parameterization	remote c
Pop-up waste set	no
power supply connection	100 - 24
position of power connection	from bott
power consumption	1.5 Volta
Type of power supply	Transfor
protective system IP	IP59K
with rosettes/cover plate	no
protective shutdown	yes
sound insulation	no
Spout	fixed

no	
0.1 l/s	
no	
24h after the last activit	у
no	
yes	
electronic self-closing	
yes	
DN 15	
G 3/8	
Top section, non-ceram	ic
brass	
1 bar	
no	
remote control	
no	
100 - 240 V AC	
from bottom	
1.5 Voltampere	
Transformer	
IP59K	
no	
yes	
no	
fixed	





## KWC F5E

Electronic pillar tap with plug-in power supply unit

## Modell-Linie: F5E | F5EV1002 Taps | Electronic taps

spout projection	125 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	no	
thermal disinfection	no	
with transformer/power supply	yes	
type of mounting	tap hole	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	pillar tap	
volume flow rate at 3 bar	0.08 l/s	
water connection	hose (gland nut)	
Accent colour	none	
Basic colour	chrome-look (glossy)	


### **Optional Accessories**





Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005



2030036849 ACEX9004

2030012758 PURE0031




Socket

2030040334 ACEX1001



Anti-twist protection for F5S

**2030035383** ACXX1001





PURETHERM under-table thermostat



5.0 l/min aerator, angle-adjustable

2030041326	
ACXX1002	



3.0 I/min. aerator

**2030041424** ASXX1008

# **2030043814** ACEX9010

Extension cable 5 m

**Spare Parts** 

KWC Group AG | Home: info@kwc.com| Professional: kwc-info.uk@kwc.com | www.kwc.com



## KWC F5E

Electronic pillar tap with plug-in power supply unit

**Modell-Linie: F5E | F5EV1002** Taps | Electronic taps



Solenoid valve cartridge

Mounting key

**2030045522** ACXX9002 **2030041329** ACXX1003