


KWC F5S-Mix Self-closing pillar mixer

Modell-Linie: F5S | F5SM1001

Taps | Self closing taps





KWC-No.

2030036163

F5S-Mix self-closing pillar mixer DN 15 as single-mixer tap for sanitary facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow volume flow rate at 3 bar

0.08 l/s

duration. With adjustable, turn-proof temperature stop. For connection to hot water and cold water via hoses with integrated backflow preventer and strainers. All-metal construction, highpolished chromium-plated brass. Anti-theft aerator, SLIM design, with integrated flow regulator 5.0 l/min.

Technical Data

| with backflow preventer | yes |
|--------------------------------|--------|
| calculation flow rate cold wat | 0.07 |
| calculation flow rate hot wate | 0.07 [|
| compatible A3000 open | no |
| depressurised | no |
| with filter | yes |
| adjustable flow time | yes |
| functional principle | hydra |
| hygiene flushing | no |
| dia meter nominal | DN 15 |
| inlet size | G 3/8 |
| Locking mechanism | Top se |
| material fitting | brass |
| maximum flow time | 35 Se |
| minimum flow pressure | 0.5 bo |
| minimum flow time | 5 Sec |
| type of mixing | yes |
| Pop-up waste set | no |
| with rosettes/cover plate | no |
| protective shutdown | no |
| sound insulation | no |
| Spout | fixed |
| spout projection | 125 n |
| surface finish fitting | chrom |
| surface treatment fitting | polish |

| yes | | |
|-------------|-------------|--|
| 0.07 l/s | | |
| 0.07 l/s | | |
| no | | |
| no | | |
| yes | | |
| yes | | |
| hydraulic : | elf-closing | |
| no | | |
| DN 15 | | |
| G 3/8 | | |
| Top sectio | n, ceramic | |
| brass | | |
| 35 Second | S | |
| 0.5 bar | | |
| 5 Seconds | | |
| yes | | |
| no | | |
| fixed | | |
| 125 mm | | |
| chromed | | |
| polished | | |





KWC F5S-Mix Self-closing pillar mixer

Modell-Linie: F5S | F5SM1001 Taps | Self closing taps

| temperature limit | yes |
|---------------------------|----------------------|
| thermal disinfection | no |
| type of mounting | tap hole |
| type of operation | manual operation |
| type of tap | pillar tap |
| volume flow rate at 3 bar | 0.08 l/s |
| water connection | hose (gland nut) |
| Accent colour | none |
| Basic colour | chrome-look (glossy) |

Optional Accessories









Socket for increasing the tap body by 140 mm

2030041519 ACSX1001

Anti-twist protection for F5S **2030035383** ACXX1001

5.0 l/min aerator, angle-adjustable

2030041326 ACXX1002

| 3.0 | l/min | aerator |
|-----|-------|---------|
| | | |

2030041424 ASXX1008

Spare Parts





Plug chromed

2030053006 ASSX9004



Safety ring

2030048357 ASSX9003



FRAMIC Self-closing mixing cartridge

2030046146 ASSM1001

Mounting key

2030041329 ACXX1003