


KWC

F3S-Mix self-closing wall-mounted mixer

Modell-Linie: F3S | F3SM1004 Taps | Self closing taps





KWC-No.	spout p
2030036196 Projection 160 mm	160 mm
2030036195 Projection 100 mm	100 mm
2030036197 Projection 220 mm	220 mm
2030039562 with projection 100 mm and aerator with flow regulator 3.0 l/min	100 mm
2030040037 with projection 160 mm and aerator with flow regulator 3.0 l/min	160 mm
2030040038 with projection 220 mm and aerator with flow regulator 3.0 l/min	220 mm

F3S-Mix self-closing wall-mounted mixer DN 15 as single-mixer tap for wall mounting with lockable swivelling spout, for sanitary facilities. Self-closing mixing cartridge, hydraulically controlled, piston-free design, self-closing, stepless adjustment of flow duration. With adjustable, turn-proof temperature stop. Connects to

pout projection	volume flow rate at 3 bar
60 mm	0.1 l/s
00 mm	0.1 l/s
20 mm	0.1 l/s
00 mm	0.05 l/s
60 mm	0.05 l/s
20 mm	0.05 l/s

hot and cold water. Casing, high-polished chromium-plated brass. Laminar jet controller with integrated flow regulator 6.0 l/min. With adjustable connections, backflow preventer, strainer seals and screw rosettes. Projection 220 mm.

Technical Data

with backflow preventer	yes
calculation flow rate cold wat	0.07 l/s
calculation flow rate hot wate	0.07 l/s
compatible A3000 open	no
depressurised	no
with filter	yes
adjustable flow time	yes
functional principle	hydraulic self-closing
hygiene flushing	no
dia meter nominal	DN 15
inlet size	G 1/2 B
Locking mechanism	Top section, non-ceramic
material fitting	brass-look
maximum flow time	20 Seconds
minimum flow pressure	1 bar
minimum flow time	5 Seconds
type of mixing	yes



кwс

F3S-Mix self-closing wall-mounted mixer

Modell-Linie: F3S | F3SM1004 Taps | Self closing taps

Pop-up waste set	no
with rosettes/cover plate	yes
protective shutdown	no
sound insulation	no
Spout	rotating, bottom
spout projection	220 mm
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	no
type of mounting	wall mounting
type of operation	manual operation
type of tap	bib tap
volume flow rate at 3 bar	0.1 V/s
water connection	S-connections
Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories





Theft-proof housing for aerator

Screw connection

2000104778 ZTAPS0005

2030041416 ACXX9001

Spare Parts











Handle push cap

Functional part

Mounting set

Swivel spout, 160 mm



кwс

F3S-Mix self-closing wall-mounted mixer

Modell-Linie: F3S | F3SM1004 Taps | Self closing taps





Laminar jet regulator

2030012352 ETAPS0037

2030032815 ASXX1002