


## KWC

F5S-Therm self-closing thermostatic wall-mounted mixer

Modell-Linie: F5S | F5ST2002

Showers | Self closing showers





duration. Thermostat with metal handle with adjustable and turn-

proof temperature stop, with the option for a manual thermal disinfection. Scald-protected Safe-Touch housing with outlet on top,

G 3/4 B, for installation of bent outlet or wall-mounted shower pipe. All-metal construction, high-polished chromium-plated brass. With adjustable and turn-proof connections with backflow preventer and strainers, completely covered with depth-adjustable screw rosettes. Version with automatic shower pipe draining.

KWC-No.	shower pipe draining
2030032978	no
2030036208 with automatic shower pipe draining	yes

F5S-Therm self-closing thermostatic wall-mounted mixer DN 15 for wall mounting, for shower facilities. Hydraulically controlled, connects to hot and cold water. With a mechanism for an optional water hygiene unit for automatic water hygiene flushing and storage of statistical data. FRAMIC self-closing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow

## Technical Data

additional connections	
with backflow preventer	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	
type of mixing	
with rosettes/cover plate	
protective shutdown	

no	
yes	
0.15 l/s	
0.15 l/s	
no	
no	
not possible	
yes	
yes	
hydraulic self-closing	
no	
prepared	
DN 15	
G 1/2 B	
Top section, ceramic	
brass	
35 Seconds	
1 bar	
5 Seconds	
with thermostat	
yes	
no	





## KWC

F5S-Therm self-closing thermostatic wall-mounted mixer

# Modell-Linie: F5S | F5ST2002 Showers | Self closing showers

shower pipe draining	yes	
sound insulation	no	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	manual thermal disinfection	
type of mounting	wall mounting	
type of operation	manual operation	
type of shower	wall fitting	
volume flow rate at 3 bar	0.3 l/s	
water connection	S-connections	
position of water connection	from backside	
Accent colour	none	
Basic colour	chrome-look (glossy)	

## **Optional Accessories**









### AQUAJET-Comfort shower head

2030021283 SHAC0008





AQUAJET-Slimline shower head

## Bent outlet

2030050434 ACXX2005



**2000103757** AQUA757

2030050435 ACXX2006

## **Spare Parts**

## Shower pipe **20** AC

30041522	
CSX2002	

### Hygiene unit for F5S-Therm

**2030041162** ACST9001



## кwс

F5S-Therm self-closing thermostatic wall-mounted mixer

# Modell-Linie: F5S | F5ST2002 Showers | Self closing showers

