


F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005

Showers | Self closing showers





KWC-No.

2030029012

2030036693

with automatic shower pipe draining

F5S-Mix self-closing single-mixer DN 15 as finished installation kit for installation in basic installation kit, for shower facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow duration. With adjustable, turn-

shower pipe draining

no

yes

proof temperature stop. Connects to hot and cold water. All-metal construction, visible parts high-polished, chromium-plated. Holding frame including profile seal, stainless steel cover plate 190 x 245 mm with covered screw fixing, chromium-plated plastic rosettes, backflow preventer and strainers. Depth adjustability 25 mm. Version with automatic shower pipe draining.

Technical Data

additional connections
with backflow preventer
Built-in fitting model
calculation flow rate cold wat
calculation flow rate hot wate
circulation
compatible A3000 open
connection with pay water disp
Cover plate height
Cover plate width
with filter
adjustable flow time
unctional principle
or hand shower
nygiene flushing
diameter nominal
nlet size
Locking mechanism
material casing
material fitting
maximum flow time
minimum flow pressure
minimum flow time

no	
yes	
Finishing section	
0.15 l/s	
0.15 l/s	
no	
no	
not possible	
245 mm	
190 mm	
yes	
yes	
hydraulic self-closing	
no	
no	
DN 15	
G 3/4 B	
Top section, ceramic	
stainless steel	
brass-look	
35 Seconds	
0.5 bar	
5 Seconds	





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

type of mixing	yes	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	yes	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	no	
type of mounting	in-wall installation with box	
type of operation	manual operation	
type of shower	in-wall fitting	
volume flow rate at 3 bar	0.2 Vs	
water connection	threaded connection (external)	
position of water connection	from side	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel-look	

Mandatory Accessories



R5 System box for in-wall mixer

2030028990 F5BX2001

Optional Accessories





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

Extension set for F5S

2030044781

ACSM2001

Spare Parts









Plug chromed

2030053006 ASSX9004





2030048356 ASSX9002



2030046188 ASSM1002









Safety ring

2030048357

ASSX9003

2030045510 ASXM2003

Rosette

FRAMIC self-closing mixing cartridge

2030046185 ASSM9001

Holding frame


2030045472 ASXX9004





2030045477 ASXM2002





2000109019 ZWSPL0024





2000105091 ZWSPL0023



F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers