


F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers





KWC-No.

2030029012

2030036693

with automatic shower pipe draining

F5S-Mix self-closing single-mixer DN 15 as finished installation kit for installation in basic installation kit, for shower facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow duration. With adjustable, turn-

shower pipe draining

yes

proof temperature stop. Connects to hot and cold water. All-metal construction, visible parts high-polished, chromium-plated. Holding frame including profile seal, stainless steel cover plate 190×245 mm with covered screw fixing, chromium-plated plastic rosettes, backflow preventer and strainers. Depth adjustability 25 mm. Version with automatic shower pipe draining.

Technical Data

additional connections	
with backflow preventer	
Built-in fitting model	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
Cover plate height	
Cover plate width	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	

no
yes
Finishing section
0.15 <i>Vs</i>
0.15 <i>Vs</i>
no
no
not possible
245 mm
190 mm
yes
yes
hydraulic self-closing
no
no
DN 15
G 3/4 B
Top section, ceramic
stainless steel
brass-look
35 Seconds
0.5 bar
5 Seconds





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

type of mixing	yes	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	yes	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	no	
type of mounting	in-wall installation with box	
type of operation	manual operation	
type of shower	in-wall fitting	
volume flow rate at 3 bar	0.2 l/s	
water connection	threaded connection (external)	
position of water connection	from side	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel-look	

Mandatory Accessories



R5 System box for in-wall mixer

2030028990 F5BX2001

Optional Accessories





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

Extension set for F5S

2030044781

ACSM2001

Spare Parts









Plug chromed

2030053006 ASSX9004

Handle push cap

2030050753 ASSM9004



2030048356 ASSX9002

Temperature stop

2030046188 ASSM1002









Safety ring

2030048357

ASSX9003

Rosette **2030045510** ASXM2003

FRAMIC self-closing mixing cartridge

2030046185 ASSM9001

Holding frame

2030045472 ASXX9004





2030045477 ASXM2002



Stainless steel care set

2000109019 ZWSPL0024



Cleaning product CHROMOL

2000105091 ZWSPL0023



F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers