


F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005

Showers | Self closing showers





KWC-No.

2030029012

2030036693

with automatic shower pipe draining

F5S-Mix self-closing single-mixer DN 15 as finished installation kit for installation in basic installation kit, for shower facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow duration. With adjustable, turn-

shower pipe draining

no

yes

proof temperature stop. Connects to hot and cold water. All-metal construction, visible parts high-polished, chromium-plated. Holding frame including profile seal, stainless steel cover plate 190 x 245 mm with covered screw fixing, chromium-plated plastic rosettes, backflow preventer and strainers. Depth adjustability 25 mm. Version with automatic shower pipe draining.

Technical Data

additional connections	
with backflow preventer	
Built-in fitting model	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
Cover plate height	
Cover plate width	
with filter	
adjustable flow time	
unctional principle	
or hand shower	
nygiene flushing	
diameter nominal	
nlet size	
Locking mechanism	
material casing	
material fitting	
maximum flow time	
ninimum flow pressure	
ninimum flow time	

Finishing section 0.15 l/s 0.15 l/s no no not possible 245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	no
0.15 l/s 0.15 l/s no no no not possible 245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	yes
0.15 l/s no no no not possible 245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	Finishing section
no not possible 245 mm 190 mm yes yes hydraulic self-closing no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	0.15 l/s
not possible 245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	0.15 l/s
not possible 245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	no
245 mm 190 mm yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	no
190 mm yes yes hydraulic self-closing no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	not possible
yes yes hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	245 mm
hydraulic self-closing ho ho DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	190 mm
hydraulic self-closing no no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	yes
no DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	yes
DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	hydraulic self-closing
DN 15 G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	no
G 3/4 B Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	no
Top section, ceramic stainless steel brass 35 Seconds 0.5 bar	DN 15
stainless steel brass 35 Seconds 0.5 bar	G 3/4 B
brass 35 Seconds 0.5 bar	Top section, ceramic
35 Seconds 0.5 bar	stainless steel
0.5 bar	brass
	35 Seconds
5 Seconds	0.5 bar
	5 Seconds





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

type of mixing	yes
with rosettes/cover plate	yes
protective shutdown	no
shower pipe draining	yes
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	no
type of mounting	in-wall installation with box
type of operation	manual operation
type of shower	in-wall fitting
volume flow rate at 3 bar	0.2 l/s
water connection	threaded connection (external)
position of water connection	from side
Accent colour	chrome-look (glossy)
Basic colour	stainless steel

Mandatory Accessories



R5 System box for in-wall mixer

2030028990 F5BX2001

Optional Accessories





F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers

Extension set for F5S

2030044781

ACSM2001

Spare Parts









Plug chromed

2030053006 ASSX9004



Guide ring

2030048356 ASSX9002



2030046188 ASSM1002









Safety ring

2030048357

ASSX9003

Rosette **2030045510** ASXM2003

FRAMIC self-closing mixing cartridge

2030046185 ASSM9001

Holding frame 2030045472 ASXX9004





2030045477 ASXM2002

Stainless steel care set

2000109019 ZWSPL0024

Cleaning product CHROMOL

2000105091 ZWSPL0023



F5S-Mix self-closing in-wall mixer

Modell-Linie: F5S | F5SM2005 Showers | Self closing showers