


F5E-Therm electronic thermostat wall-mounted mixer for separate power supply

Modell-Linie: F5E | F5ET2005

Showers | Electronic self closing shower





KWC-No.

2030039542

2030039550

Version with pre-assembled thermal disinfection unit

F5E-Therm thermostatic mixer DN 15 for wall mounting, for shower facilities. Electronically controlled, for connection to hot water and cold water. Thermostat with metal handle and adjustable, turn-proof temperature stop. With option for thermal disinfection, manually or automatically via optional disinfection unit. Control electronics, solenoid valve cartridge and touch sensor in scald-protected safe-touch housing with outlet on top, G 3/4 B, for installation of bent outlet or surface-mounted shower pipe. All-metal

thermal disinfection

yes

automatic thermal disinfection

construction, high-polished chromium-plated brass. With adjustable and lockable connections with backflow preventer and strainers, completely covered with depth-adjustable screw rosettes. Activated water hygiene flushing 24 hours after last activation and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. Separate power supply via power supply unit 6.75 V / 12 V DC or AQUA 3000 open system accessories.

Technical Data

Technical Data	
additional connections	
with backflow preventer	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
default flow time	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	

no	
yes	
0.15 l/s	
0.15 l/s	
no	
yes	
via electronic module	
24h after the last activity	
30 Seconds	
yes	
yes	
electronic self-closing	
no	
yes	
DN 15	
G 1/2 B	
Top section, non-ceramic	
brass	
brass	
255 Seconds	
1 bar	
1 Seconds	















F5E-Therm electronic thermostat wall-mounted mixer for separate power supply

Modell-Linie: F5E | F5ET2005


Showers | Electronic self closing shower

type of mixing	with thermostat
Parameterization	remote control
power supply connection	6,75 / 12 V DC / A3000 open
position of power connection	from backside
power consumption	1.5 Voltampere
Type of power supply	Transformer
with rosettes/cover plate	yes
protective shutdown	yes
shower pipe draining	no
sound insulation	no
surface finish casing	chromed
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	wall mounting
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of shower	wall fitting
Volume flow rate bypass PWH	0.05 l/s
volume flow rate at 3 bar	0.23 l/s
water connection	S-connections
position of water connection	from backside
Accent colour	none
Basic colour	chrome-look (glossy)

Mandatory Accessories







Mounting bar for F5 wall-mounted mixers

2030071303 F5BTX002 Power supply unit

2030039477 ACEX9001 Extension cable 5 m

2030043814 ACEX9010

Optional Accessories



F5E-Therm electronic thermostat wall-mounted mixer for separate power supply

Modell-Linie: F5E | F5ET2005

Showers | Electronic self closing shower









Bent outlet

2030050434 ACXX2005



2030050435 ACXX2006

Shower pipe

2030041525 ACXX2003

AQUAJET-Slimline shower head

2000103757 AQUA757









AQUAJET-Comfort shower head

2030021283 SHAC0008

Thermal disinfection unit for F5E-Therm thermostatic wall mixers

2030039541 ACET9001

Electronic module EM5 for F5 shower

2030041918 ACET2001

Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005



2-button remote control for fittings F3 and F5

2030036849

ACEX9004


Spare Parts



F5E-Therm electronic thermostat wall-mounted mixer for separate power supply

Modell-Linie: F5E | F5ET2005 Showers | Electronic self closing shower





Temperature stop

2030003296 EAQLT0003

Solenoid valve cartridge

2030003033 EAQFU0001