


KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022

Taps | Electronic taps





KWC-No.

2030036177

2030040224

with flow regulator 3.0 l/min

F3E bib tap DN 15 for wall mounting for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, high-polished chromium-plated brass. Aerator with integrated flow regulator 3.0

volume flow rate at 3 bar

0.1 1/s

0.05 l/s

l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Technical Data

reciliiedi bata	
with backflow preventer	
calculation flow rate cold wat	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
number of batteries	
Parameterization	
Pop-up waste set	
power supply connection	
power consumption	
Type of power supply	
protective system IP	
with rosettes/cover plate	
protective shutdown	
sound insulation	
Spout	

no	
0.1 l/s	
no	
24h after the last activity	
no	
yes	
electronic self-closing	
yes	
DN 15	
Top section, non-ceramic	
brass-look	
1 bar	
no	
1	
remote control	
no	
Battery 6 V	
1.5 Voltampere	
Battery	
IP59K	
no	
yes	
no	
fixed	









KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022 Taps | Electronic taps

spout projection	130 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	no	
thermal disinfection	automatic thermal disinfection	
with transformer/power supply	no	
type of batteries	CR-P2 Lithium battery 6V	
type of mounting	wall mounting	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	bib tap	
volume flow rate at 3 bar	0.05 l/s	
water connection	threaded connection (external)	
Accent colour	none	
Basic colour	chrome-look (glossy)	

Optional Accessories









Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

Extension adapter for F3E bib tap

2030043823 ACEV1001

Theft-proof housing for aerator

2000104778 ZTAPS0005



Aerator 6.0 I/min

2000104691 ASXX1015



KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022 Taps | Electronic taps

Spare Parts









Cover cap

2030049344 ASEV1004



2000104846 EPRTR0008

Solenoid valve cartridge

2030045522 ACXX9002

Sensor, ID 01/00001

2030041447 ASEX1001









3.0 I/min. aerator

2030041424 ASXX1008

Spare part set

2030042426 ASEX1011

2030042439 ASEV1002

O-ring, red O-ring, blue

2030042440 ASEV1002