


KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022

Taps | Electronic taps





KWC-No.

2030036177

2030040224

with flow regulator 3.0 l/min

F3E bib tap DN 15 for wall mounting for sanitary facilities, optoelectronically controlled. For connection to pre-mixed hot or cold water. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, high-polished chromium-plated brass. Aerator with integrated flow regulator 3.0

volume flow rate at 3 bar

0.1 1/s

0.05 l/s

l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Technical Data

Technical Data		
with backflow preventer		
calculation flow rate cold wat		
compatible A3000 open		
default automatic hygiene flus		
depressurised		
with filter		
functional principle		
hygiene flushing		
diameter nominal		
Locking mechanism		
material fitting		
minimum flow pressure		
type of mixing		
number of batteries		
Parameterization		
Pop-up waste set		
power supply connection		
power consumption		
Type of power supply		
protective system IP		
with rosettes/cover plate		
protective shutdown		
sound insulation		
Spout		

no	
0.1 l/s	
no	
24h after the last activity	
no	
yes	
electronic self-closing	
yes	
DN 15	
Top section, non-ceramic	
brass	
1 bar	
no	
1	
remote control	
no	
Battery 6 V	
1.5 Voltampere	
Battery	
IP59K	
no	
yes	
no	
fixed	









KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022

Taps | Electronic taps

spout projection	130 mm
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	no
thermal disinfection	automatic thermal disinfection
with transformer/power supply	no
type of batteries	CR-P2 Lithium battery 6V
type of mounting	wall mounting
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of tap	bib tap
volume flow rate at 3 bar	0.05 l/s
water connection	threaded connection (external)
Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories







Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005 2-button remote control for fittings F3 and F5

2030036849 ACEX9004 Extension adapter for F3E bib tap

2030043823 ACEV1001

Spare Parts





Solenoid valve cartridge

2030045522

3.0 I/min. aerator

2030041424



KWC

F3E electronic bib tap with battery operation

Modell-Linie: F3E | F3EV1022 Taps | Electronic taps

ACXX9002	ASXX1008