



## **KWC** F5S-Mix Self-closing wall-mounted mixer

## Modell-Linie: F5S | F5SM1008

Taps | Self closing taps







## KWC-No.

#### 2030032992

Projection 195 mm

#### 2030032991

Projection 135 mm

**2030032993** Projection 255 mm

## 2030040314

with projection 135 mm and aerator with flow regulator 3.0  $\mbox{\emph{l}/min}$ 

with projection 195 mm and aerator with flow regulator 3.0 l/min

## 2030040317

with projection 255 mm and aerator with flow regulator 3.0 l/min

F5S mix self-closing wall-mounted mixer DN 15 as single-mixer tap for wall mounting with lockable swivelling spout, for sanitary facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow duration. With

#### spout projection

## volume flow rate at 3 bar

195 mm	0.1 l/s
135 mm	0.1 l/s
255 mm	0.1 l/s
135 mm	0.05 l/s
195 mm	0.05 l/s
255 mm	0.05 l/s

adjustable, turn-proof temperature stop. Connects to hot and cold water. All-metal construction, high-polished chromium-plated brass. Aerator with an integrated flow regulator 3.0 l/min. With adjustable and lockable connections with backflow preventer and strainers, completely covered with depth-adjustable screw rosettes. Projection 135 mm.

## **Technical Data**

with backflow preventer
calculation flow rate cold wat
calculation flow rate hot wate
compatible A3000 open
depressurised
with filter
adjustable flow time
functional principle
hygiene flushing
diameter nominal
inlet size
Locking mechanism
material fitting
maximum flow time
minimum flow pressure
minimum flow time
type of mixing

yes	
0.07 l/s	
0.07 l/s	
no	
no	
yes	
yes	
hydraulic self-closing	
no	
DN 15	
G 1/2 B	
Top section, ceramic	
brass-look	
35 Seconds	
0.5 bar	
5 Seconds	
yes	





## **KWC** F5S-Mix Self-closing wall-mounted mixer

# Modell-Linie: F5S | F5SM1008 Taps | Self closing taps

Pop-up waste set	no	
with rosettes/cover plate	yes	
protective shutdown	no	
sound insulation	no	
Spout	rotating, bottom	
spout projection	135 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	no	
type of mounting	wall mounting	
type of operation	manual operation	
type of tap	bib tap	
volume flow rate at 3 bar	0.05 l/s	
water connection	S-connections	
Accent colour	none	
Basic colour	chrome-look (glossy)	

## **Optional Accessories**



## Theft-proof housing for aerator

**2000104778** ZTAPS0005

## **Spare Parts**









Screw rosette

Mounting set

Handle push cap

Temperature stop



## **KWC** F5S-Mix Self-closing wall-mounted mixer

# Modell-Linie: F5S | F5SM1008 Taps | Self closing taps

**2030046777** ASXX9003



**2030003401** EAQLT0009







Safety ring

**2030048357** ASSX9003

FRAMIC self-closing mixing cartridge

**2030046185** ASSM9001

3.0 I/min. aerator

**2030041424** ASXX1008

Swivel spout, 40 mm

**2030049950** ASXX1009



## Plug chromed

**2030053006** ASSX9004