


KWC F5S-Mix Self-closing wall-mounted mixer

Modell-Linie: F5S | F5SM1008
Taps | Self closing taps



KWC-No.

2030032992

Projection 195 mm

2030032991

Projection 135 mm

2030032993

Projection 255 mm

2030040314

with projection 135 mm and aerator with flow regulator 3.0 l/min

2030040316

with projection 195 mm and aerator with flow regulator 3.0 l/min

2030040317

with projection 255 mm and aerator with flow regulator 3.0 l/min

spout projection

195 mm

135 mm

255 mm

135 mm

195 mm

255 mm

volume flow rate at 3 bar

0.1 l/s

0.1 l/s

0.1 l/s

0.05 l/s

0.05 l/s

0.05 l/s

F5S mix self-closing wall-mounted mixer DN 15 as single-mixer tap for wall mounting with lockable swivelling spout, for sanitary facilities. FRAMIC self-closing mixing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium-separated design. Stepless adjustment of flow duration. With

adjustable, turn-proof temperature stop. Connects to hot and cold water. All-metal construction, high-polished chromium-plated brass. Aerator with an integrated flow regulator 3.0 l/min. With adjustable and lockable connections with backflow preventer and strainers, completely covered with depth-adjustable screw rosettes. Projection 135 mm.

Technical Data

with backflow preventer

yes

calculation flow rate cold wat

0.07 l/s

calculation flow rate hot wate

0.07 l/s

compatible A3000 open

no

depressurised

no

with filter

yes

adjustable flow time

yes

functional principle

hydraulic self-closing

hygiene flushing

no

diameter nominal

DN 15

inlet size

G 1/2 B

Locking mechanism

Top section, ceramic

material fitting

brass

maximum flow time

35 Seconds

minimum flow pressure

0.5 bar

minimum flow time

5 Seconds

type of mixing

yes



KWC F5S-Mix Self-closing wall-mounted mixer

Modell-Linie: F5S | F5SM1008
Taps | Self closing taps

Pop-up waste set	no
with rosettes/cover plate	yes
protective shutdown	no
sound insulation	no
Spout	rotating, bottom
spout projection	135 mm
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	no
type of mounting	wall mounting
type of operation	manual operation
type of tap	bib tap
volume flow rate at 3 bar	0.05 l/s
water connection	S-connections
Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories



Theft-proof housing for aerator

2000104778
ZTAPS0005

Spare Parts



Screw rosette



Mounting set



Handle push cap



Temperature stop

KWC F5S-Mix Self-closing wall-mounted mixer

Modell-Linie: F5S | F5SM1008
Taps | Self closing taps

2030046777
ASXX9003



Safety ring

2030048357
ASXX9003



Plug chromed

2030053006
ASXX9004

2030003401
EAQLT0009



FRAMIC self-closing mixing cartridge

2030046185
ASSM9001


2030050753
ASSM9004



3.0 l/min. aerator

2030041424
ASXX1008

2030046189
ASSM9002



Swivel spout, 40 mm

2030049950
ASXX1009