


#### Modell-Linie: F5S | F5ST2020

Showers | Self closing showers





#### KWC-No.

#### 2030055929

F5S Therm shower panel made of stainless steel for wall mounting with DN 15 self-closing thermostatic mixer and connecting nozzles for the shower head. Hydraulically controlled, for connection to hot water and cold water. Shower valve with integrated FRAMIC self-closing cartridge, thermostat and pre-assembled hygiene unit including sensor with control electronics to perform automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge required) and storage of statistical data. FRAMIC self-closing cartridge, low maintenance and stagnation free, with ceramic disc technology, self-closing, flow pressure independent due to the medium-independent design. Stepless adjustment of flow duration. Thermostat with metal handle, an adjustable and turn-proof temperature stop and an option for manual thermal disinfection. All-metal construction, visible parts high-polished or chrome-plated.

Connecting nozzles for the required additional DN 15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Housing made of stainless steel with raised function surface and plastic cover caps. Connecting hoses with lockable water volume control with backflow preventer and strainer. Activated water hygiene flushing at fixed intervals of 24 hours. With option for parameterization and communication via the optional bidirectional remote control. Optional hygiene unit for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via plug-in power supply unit 6.75 V/12 V DC.

Dimensions of housing 235 x 1160 x 90 mm (W x H x D)

Shower head and battery compartment including battery or plug-in power supply unit with extension cable to be ordered separately.

# Technical Data

Technical Data		
additional connections		
with backflow preventer		
circulation		
compatible A3000 open		
connection with pay water disp		
default automatic hygiene flus		
with filter		
adjustable flow time		
functional principle		
for hand shower		
hygiene flushing		
diameter nominal		
inlet size		
Locking mechanism		
material casing		
material code casing		
material fitting	·	
maximum flow time	<u>-</u>	
minimum flow pressure		
minimum flow time		

no	
yes	
no	
no	
not possible	
fixed interval 24 hours	
yes	
yes	
hydraulic self-closing	
no	
yes	
DN 15	
G 1/2 A	
Top section, ceramic	
stainless steel	
1.4301 Chrome Nickel steel V2	A
brass-look	
35 Seconds	
1.5 bar	
5 Seconds	·











# Modell-Linie: F5S | F5ST2020 Showers | Self closing showers

type of mixing	with thermostat	
overall depth	90 mm	
overall height	1,160 mm	
overall width	235 mm	
Parameterization	remote control	
power supply connection	6,75 / 12 V D C	
position of power connection	from top / backside	
Type of power supply	Other	
protective system IP	IP59K	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	no	
Shower head	for separately shower head	
with shower set	no	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	yes	
with transformer/power supply	no	
type of mounting	wall mounting	
type of operation	manual operation	
type of sensor	opto-electronic sensor	
type of shower	shower panel	
volume flow rate at 3 bar	0.15 l/s	
water connection	hose (gland nut)	
position of water connection	from top / backside	
with soap dish	no	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel-look	

### **Mandatory Accessories**









AQUAJET-Slimline shower head for KWC shower panels and systems

**2030054255** SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

**2030054254** SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

**2030054793** SHMU0011

Battery compartment


**3600002063** ACEX9023



Modell-Linie: F5S | F5ST2020

Showers | Self closing showers





Power supply unit

2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

#### **Optional Accessories**









Flow controller 6.0 I/min

**2030027586** ESHHE0004

Flow controller 12.0 I/min

**2000104783** ESHHE0002


Set for thermal disinfection


**2030057940** ACXT2001

Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005









2-button remote control for fittings F3 and F5

**2030036849** ACEX9004

Housing extension for F5 shower panels made of stainless steel

**2030057066** ACXX2011

Housing extension for F5 shower panels made of stainless steel

**2030057067** ACXX2012

Housing extension for F5 shower panels made of stainless steel

**2030057068** ACXX2013




Modell-Linie: F5S | F5ST2020

Showers | Self closing showers









Housing extension for F5 shower panels made of stainless steel

**2030057069** ACXX2014 Housing extension for F5 shower panels made of stainless steel

**2030057070** ACXX2015 Shower gel dish for F5 shower panels made of stainless steel

**2030057077** ACXX2021 Connection set for shower panel

**2000104916** ZSHOW0006



#### Connection adapter

**2000101441** AQRM928

# **Spare Parts**





**2000104782** ESHHE0001



Cover

**2030031443** ESHOW0059



# Temperature handle

**2030047082** ASXT9003



# Temperature stop

**2030003296** EAQLT0003



Modell-Linie: F5S | F5ST2020 Showers | Self closing showers










Plug chromed

**2030053006** ASSX9004





**2030049943** ASST2001



Safety ring

**2030048357** ASSX9003




Rosette

**2030048765** ASET2006



FRAMIC Self-closing cartridge

**2030046145** ASSX9001



**2030003033** EAQFU0001



Stainless steel care set

**2000109019** ZWSPL0024



Cleaning product CHROMOL

**2000105091** ZWSPL0023