


KWC F5E-Therm

Shower panel made of MIRANIT with shower gel shelf

Modell-Linie: F5E | F5ET2026

Showers | Electronic self closing shower





KWC-No.

2030056574

F5E Them shower panel made of mineral material for wall mounting with thermostatic mixer and connecting nozzles for the shower head. Electrically controlled, for connection to hot water and cold water. Shower valve with integrated solenoid valve cartridge, thermostat and mechanism for optional bypass solenoid valve cartridge to perform program-controlled thermal disinfection. Thermostat with metal handle, an adjustable and tum-proof temperature stop and an option for manual thermal disinfection. Allmetal construction, visible parts high-polished or chrome-plated. Connecting nozzles for the required additional DN 15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Housing with raised function surface and seamless moulded shower gel shelf made of MIRANIT resin-bonded mineral material with pore-free smooth surface (temperature-resistant up to 80 °C), Alpine white colour. Button sensor including control electronics with start/stop function and deactivation for cleaning. Connecting hoses with lockable water volume control with backflow preventer and strainer. Activated water hygiene flushing 24 hours after last activation and saving of statistical data. With option for parameterization and communication via the optional bidirectional remote control. Battery operation with 6 V lithium battery (CR-P2) per fitting, separate power supply via plug-in power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.


Dimensions of housing $235 \times 1160 \times 100$ mm (W x H x D)

Shower head and battery compartment including battery or plug-in power supply unit with extension cable to be ordered separately.

Technical Data

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
default flow time	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
maximum flow time	
minimum flow pressure	

no	
yes	
no	
yes	
via electronic module	
24h after the last activity	
30 Seconds	
yes	
yes	
electronic self-closing	
no	
yes	
DN 15	
G 1/2 A	
Top section, non-ceramic	
mineral material	
Miranit	
brass-look	
255 Seconds	
1.5 bar	





Modell-Linie: F5E | F5ET2026 Showers | Electronic self closing shower

minimum flow time	1 Seconds
type of mixing	with thermostat
overall depth	100 mm
overall height	1,160 mm
overall width	235 mm
Parameterization	remote control
power supply connection	6,75 / 12 V DC / A3000 open
position of power connection	from top / backside
Type of power supply	Other
with rosettes/cover plate	yes
protective shutdown	yes
shower pipe draining	no
Shower head	for separately shower head
with shower set	no
sound insulation	no
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	wall mounting
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of shower	shower panel
volume flow rate at 3 bar	0.15 l/s
water connection	hose (gland nut)
position of water connection	from top / backside
with soap dish	integrated
Accent colour	chrome-look (glossy)
Basic colour	white

Mandatory Accessories









AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011

Battery compartment


3600002063 ACEX9023



Modell-Linie: F5E | F5ET2026

Showers | Electronic self closing shower





Power supply unit

2030039477 ACEX9001 Extension cable 5 m

ACEX9010

Optional Accessories



Flow controller 6.0 l/min

2030027586 ESHHE0004



Flow controller 12.0 l/min

2000104783 ESHHE0002



Set for thermal disinfection

2030057940 ACXT2001



Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005







and F5

2030036849	,
ACEX9004	

Housing extension for F5 shower panels made of MIRANIT

2030057071 ACXX2016 Housing extension for F5 shower panels made of MIRANIT

2030057072 ACXX2017 Housing extension for F5 shower panels made of MIRANIT

2030057073 ACXX2018



Modell-Linie: F5E | F5ET2026

Showers | Electronic self closing shower





Housing extension for F5 shower panels made of MIRANIT

2030057075 ACXX2019



Housing extension for F5 shower panels made of MIRANIT

2030057076 ACXX2020



Electronic module EM5 for F5 shower taps

2030041918 ACET2001



Connection set for shower panel

2000104916 ZSHOW0006



Connection adapter

2000101441 AQRM928

Spare Parts

Cover

2030031443 ESHOW0059





Temperature handle

2030047082 ASXT9003



Temperature stop

2030003296 EAQLT0003



Solenoid valve cartridge

2030003033 EAQFU0001



Modell-Linie: F5E | F5ET2026 Showers | Electronic self closing shower



Flow controller 9,0 l/min

2000104782 ESHHE0001