


#### **KWC** F5E-Mix

## Electronic washbasin mixer for fitting unit or wall flange

#### Modell-Linie: F5E | F5EM1015

Taps | Electronic taps





#### KWC-No.

#### 2030058995

F5E-Mix Electronic washbasin mixer

F5E-Mix Washbasin mixer DN 15 with angled outlet for installation on fitting units or separate wall flanges, for sanitary facilities. Optoelectronic control, activation on hand reflection. For connection to hot and cold water. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, highpolished chrome-plated brass. Temperature lever with adjustable, turn-proof temperature stop. Anti-theft aerator, SLIM design, with

integrated flow regulator 5.0 l/min. Connections positioned above one another with backflow preventers. Activated water hygiene flushing 24 hours after last activation, safety switch-off for continuous reflexion and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

#### Technical Data

with backflow preventer	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
adjustable flow time	
functional principle	
hygiene flushing	
diameter nominal	
Locking mechanism	·
material fitting	
minimum flow pressure	
type of mixing	
number of batteries	
Parameterization	
Pop-up waste set	
power supply connection	
Type of power supply	
with rosettes/cover plate	
protective shutdown	
sound insulation	
Spout	·
spout projection	·
surface finish fitting	

yes	
no	
24h after the last activity	/
no	
yes	
yes	
electronic self-closing	
yes	
DN 15	
Top section, non-ceramic	
brass	
1 bar	
yes	
1	
remote control	
no	
Battery 6 V	
Battery	
no	
yes	
no	
fixed	
110 mm	
chromed	









#### **KWC** F5E-Mix

## Electronic washbasin mixer for fitting unit or wall flange

#### Modell-Linie: F5E | F5EM1015

Taps I Electronic taps

surface treatment fitting	polished
temperature limit	yes
thermal disinfection	automatic thermal disinfection
with transformer/power supply	no
type of batteries	CR-P2 Lithium battery 6V
type of mounting	mounted on product
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of tap	for fitting unit
volume flow rate at 3 bar	0.08 l/s
water connection	plug connection
Accent colour	none
Basic colour	chrome-look (glossy)

#### **Mandatory Accessories**







Wall flange

**2030058762** ACXM1002 Single clamping bridge

**2030058826** ACXM1003

## Double clamping bridge

**2030059971** ACXM1004

### **Optional Accessories**









Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005



**2030036849** ACEX9004 5.0 l/min aerator, angle-adjustable

**2030041326** ACXX1002 3.0 I/min. aerator

**2030041424** ASXX1008



## **KWC** F5E-Mix

Electronic washbasin mixer for fitting unit or wall flange

# Modell-Linie: F5E | F5EM1015 Taps | Electronic taps

## **Spare Parts**





#### Solenoid valve cartridge

**2030045522** ACXX9002

## Mounting key

**2030041329** ACXX1003