


KWC F5E
Washbasin fitting for concealed mounting

Modell-Linie: F5E | F5EV1013
Taps | Electronic taps



KWC-No.

2030062315

F5E Washbasin fitting DN 15 for concealed mounting. Opto-electronic control, activation on hand reflection. For connection to pre-mixed hot water or cold water. With round sensor (diameter 55 mm), with integrated control electronics and deactivation of cleaning, high-polished chrome-plated brass, to be screwed in from rear, with anti-twist protection, solenoid valve with screw fixings G 1/2 B, extension cable for solenoid valve, length 5 m. Activated water hygiene flushing 24 hours after last activation and saving of


statistical data. With option for parameterization and communication via optional, bidirectional remote control. Optional battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

with backflow preventer
compatible A3000 open
default automatic hygiene flus
depressurised
with filter
functional principle
hygiene flushing
diameter nominal
inlet size
Locking mechanism
material casing
material fitting
minimum flow pressure
type of mixing
Parameterization
Pop-up waste set
power supply connection
Type of power supply
with rosettes/cover plate
protective shutdown
sound insulation
surface finish fitting
surface treatment fitting

no
yes
24h after the last activity
no
no
electronic self-closing
yes
DN 15
G 1/2 B
Top section, non-ceramic
brass
synthetic
1 bar
no
remote control
no
6,75 / 12 V DC / A3000 open
Transformer
no
yes
no
chromed
polished





KWC F5E
Washbasin fitting for concealed mounting

Modell-Linie: F5E | F5EV1013
Taps | Electronic taps

temperature limit	no
thermal disinfection	no
with transformer/power supply	no
type of mounting	concealed
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of tap	in-wall tap
water connection	threaded connection (external)
Accent colour	none

Mandatory Accessories



Power supply unit

2030039477
ACEX9001

Extension cable 5 m

2030043814
ACEX9010

Optional Accessories



Bidirectional remote control for
electronical fittings F3 and F5

2030036654
ACEX9005

2-button remote control for fittings F3
and F5

2030036849
ACEX9004

Electronic module EM5 for F5
washbasin fitting

2030065092
ACEV1002

Cover plate

2000101054
ZAQUA084