


Shower panel made of MIRANIT with diverter between overhead shower and hand shower

Modell-Linie: F5E | F5ET2050

Showers | Electronic self closing shower





KWC-No.

2030062975

F5E-Therm shower panel made of mineral material for wall mounting with thermostatic mixer and diverter between overhead shower and hand shower. Electrically controlled, connects to hot water and cold water. Function block with integrated solenoid valve cartridge, thermostat and mechanism for optional bypass solenoid valve cartridge to perform program-controlled thermal disinfection. Thermostat with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts polished chrome-plated. Connecting nozzles for separately required DN 15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Housing with raised function surface made of MIRANIT resin-bonded mineral material with pore-free smooth surface (temperature-resistant up to 80 °C), Alpine white colour. Hand shower connection on the left and chrome-plated plastic hand shower holder on the right, both pre-assembled

on the side. Button sensor including control electronics with start/stop function and deactivation of cleaning. Connector hoses with lockable water flow control with backflow preventer and strainer. Activated water hygiene flushing 24 hours after last activation and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. Optionally for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via 6.75 V/12 V DC power supply unit or AQUA 3000 open system accessories.

Housing dimensions 235 x 1160 x 100 mm (W x H x D)

Shower head, hand shower with shower hose and battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

Technical Data	
additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
default flow time	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
maximum flow time	·
minimum flow pressure	

for handshower with sw	itch
yes	
no	
yes	
via electronic module	
24h after the last activity	/
30 Seconds	
yes	
yes	
electronic self-closing	
yes	
yes	
DN 15	
G 1/2 A	
Top section, non-cerami	
mineral material	·
Miranit	
brass	
255 Seconds	
1.5 bar	·















Shower panel made of MIRANIT with diverter between overhead shower and hand shower

Modell-Linie: F5E | F5ET2050

Showers | Electronic self closing shower

minimum flow time	1 Seconds
type of mixing	with thermostat
overall depth	100 mm
overall height	1,160 mm
overall width	235 mm
Parameterization	remote control
power supply connection	6,75 / 12 V DC / A3000 open
position of power connection	from top / backside
Type of power supply	Other
with rosettes/cover plate	yes
protective shutdown	yes
shower pipe draining	no
Showerhead	for separately shower head
with shower set	no
sound insulation	no
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	wall mounting
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of shower	shower panel
volume flow rate at 3 bar	0.15 <i>l</i> /s
water connection	hose (gland nut)
position of water connection	from top / backside
with soap dish	no
Accent colour	chrome-look (glossy)
Basic colour	white

Mandatory Accessories









AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011 AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011 MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011 Power supply unit


2030039477 ACEX9001



Shower panel made of MIRANIT with diverter between overhead shower and hand shower

Modell-Linie: F5E | F5ET2050

Showers | Electronic self closing shower



Extension cable 5 m

2030043814 ACEX9010

Optional Accessories









Flow controller 6.0 I/min

2030027586 ESHHE0004



2000104783 ESHHE0002



2030051216 ACXX2007


Shower bracket

2030051217 ACXX2008









Set for thermal disinfection

2030057940

ACXT2001

Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3

2030036849 ACEX9004

Housing extension for F5 shower panels made of MIRANIT

2030057071 ACXX2016



Shower panel made of MIRANIT with diverter between overhead shower and hand shower

Modell-Linie: F5E | F5ET2050

Showers | Electronic self closing shower









Housing extension for F5 shower panels made of MIRANIT

2030057072 ACXX2017

Housing extension for F5 shower panels made of MIRANIT

2030057073 ACXX2018


Housing extension for F5 shower panels made of MIRANIT

2030057075 ACXX2019

Housing extension for F5 shower panels made of MIRANIT

2030057076 ACXX2020





Electronic module EM5 for F5 shower taps

2030041918 ACET2001

Connection set for shower panel

2000104916 ZSHOW0006











Flow controller 9,0 I/min

2000104782 ESHHE0001

Cover

2030031443 ESHOW0059

Temperature handle

2030047082 ASXT9003

Temperature stop

2030003296 EAQLT0003



Shower panel made of MIRANIT with diverter between overhead shower and hand shower

Modell-Linie: F5E | F5ET2050 Showers | Electronic self closing shower



Solenoid valve cartridge

2030003033 EAQFU0001