


KWC F5L-Therm

Single-lever thermostatic mixer for tap unit or wall flange

Modell-Linie: F5L | F5LT1033

Taps | Manual taps





KWC-No.

2030065268

F5L-Therm single-lever thermostatic mixer

F5L-Therm single-lever thermostatic mixer DN 15 with slanted drain for mounting on tap unit or separate wall flange, for sanitary facilities. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. For connection to hot and cold water. All-metal construction, high-polished chrome-plated brass. Anti-theft aerator, SLIM design, with integrated flow regulator 5.0 l/min. Connections positioned above one another with backflow preventers.

Technical Data

with backflow preventer	yes		
calculation flow rate cold wat	0.06 l/s		
calculation flow rate hot wate	0.06 l/s		
depressurised	no		
with filter	yes		
functional principle	manual		
hygiene flushing	no		
diameter nominal	DN 15		
Locking mechanism	Top section, non-ceramic		
material fitting	brass-look		
minimum flow pressure	1 bar		
type of mixing	with thermostat		
Pop-up waste set	no		
with rosettes/cover plate	no		
protective shutdown	yes		
sound insulation	no		
Spout	fixed		
spout projection	110 mm		
surface finish fitting	chromed		
surface treatment fitting	polished		
temperature limit	yes		
thermal disinfection	no		
type of mounting	mounted on product		
type of operation	manual operation		
type of tap	for fitting unit		





KWC F5L-Therm

Single-lever thermostatic mixer for tap unit or wall flange

Modell-Linie: F5L | F5LT1033 Taps | Manual taps

volume flow rate at 3 bar	0.08 l/s	
water connection	plug connection	
Accent colour	none	
Basic colour	chrome-look (glossy)	

Mandatory Accessories







Double clamping bridge

2030059971 ACXM1004

Wall flange

Single clamping bridge **2030058826** ACXM1003

2030058762 ACXM1002

Optional Accessories







5.0 l/min aerator, angle-adjustable

3.0 l/min. aerator

2030041326 ACXX1002

k

2030041424 ASXX1008

Aerator	1.8	l/min	
		~	

2030041442 ACXX1005

Spare Parts



KWC F5L-Therm Single-lever thermostatic mixer for tap unit or wall flange

Modell-Linie: F5L | F5LT1033 Taps | Manual taps







Guide bushing

2030023924 ETAPS0040 Aerator 5.0 l/min

2030041011 ASXX1004 Mounting key

2030041329 ACXX1003