


KWC F5L-Therm Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT2001

Showers | Manual shower







KWC-No.

2030066495

F5L-Therm thermostatic single-lever mixer as DN 15 wall-mounted mixer for wall mounting, for shower facilities. Thermostaticallycontrolled mixer cartridge with expansion element and active scald protection as well as adjustable and tum-proof temperature stop, and ceramic disc technology. With mechanism for optional hygiene unit for automatic hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. For connection to hot and cold water. Scald-protection Safe-Touch housing with outlet on top, G 3/4 B, for installation of waste elbow or wallmounted shower pipe. All-metal construction, high-polished chrome-plated brass. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depthadjustable screw rosettes.

Technical Data

additional connections	no
with backflow preventer	yes
circulation	no
connection with pay water disp	not pos
with filter	yes
functional principle	manuc
for hand shower	no
hygiene flushing	prepai
dia meter nominal	DN 15
inlet size	G 1/2 I
Locking mechanism	Top se
material casing	brass-
material fitting	brass-
minimum flow pressure	1 bar
type of mixing	with th
with rosettes/cover plate	yes
protective shutdown	no
shower pipe draining	no
sound insulation	no
surface finish casing	chrome
surface finish fitting	chrome
surface treatment fitting	polishe
temperature limit	yes
thermal disinfection	yes

no	
yes	
no	
not possible	
yes	
manual	
no	
prepared	
DN 15	
G 1/2 B	
Top section, ceramic	
brass-look	
brass-look	
1 bar	
with thermostat	
yes	
no	
no	
no	
chromed	
chromed	
polished	
yes	
yes	





KWC F5L-Therm Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT2001

Showers | Manual shower

type of mounting	wall mounting	
type of operation	manual operation	
type of shower	wall fitting	
volume flow rate at 3 bar	0.25 \/s	
water connection	S-connections	
position of water connection	from backside	
Accent colour	none	
Basic colour	chrome-look (glossy)	

Optional Accessories





AQUAJET-Slimline shower head





Bent outlet

2030050435

ACXX2006

AQUAJET-Comfort shower head

2030021283 SHAC0008







Hygiene unit for F5L single-lever wall mixers

2030039446 ACLM9001



Bent outlet

2030050434

ACXX2005

Solenoid valve cartridge

2030045522 ACXX9002

Spare Parts

Shower pipe

2030041525

ACXX2003



2000103757 AQUA757

KWC Group AG | Home: info@kwc.com| Professional: kwc-export.int@kwc.com | www.kwc.com



KWC F5L-Therm Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT2001 Showers | Manual shower





Mounting set

2030003401 EAQLT0009 Screw rosette

2030046777 ASXX9003