


KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT2001

Showers | Manual shower





KWC-No.

2030066495

F5L-Therm thermostatic single-lever mixer as DN 15 wall-mounted mixer for wall mounting, for shower facilities. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. With mechanism for optional hygiene unit for automatic hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve

cartridge necessary) and storage of statistical data. For connection to hot and cold water. Scald-protection Safe-Touch housing with outlet on top, G 3/4 B, for installation of waste elbow or wall-mounted shower pipe. All-metal construction, high-polished chrome-plated brass. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes.

Technical Data

additional connections	
with backflow preventer	
circulation	
connection with pay water disp	
with filter	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material fitting	
minimum flow pressure	
type of mixing	
with rosettes/cover plate	
protective shutdown	
shower pipe draining	
sound insulation	
surface finish casing	
surface finish fitting	
surface treatment fitting	
temperature limit	
thermal disinfection	

no	
yes	
no	
not possible	
yes	
manual	
no	
prepared	
DN 15	
G 1/2 B	
Top section, ceramic	
brass	
brass	
1 bar	
with thermostat	
yes	
no	
no	
no	
chromed	
chromed	
polished	
yes	
yes	







KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT2001

Showers | Manual shower

type of mounting	wall mounting
type of operation	manual operat
type of shower	wall fitting
volume flow rate at 3 bar	0.25 l/s
water connection	S-connections
position of water connection	from backside
Accent colour	none
Basic colour	chrome-look (g

manual operation		
wall fitting		
0.25 l/s		
S-connections		
from backside		
none		

Optional Accessories









AQUAJET-Comfort shower head

2030021283 SHAC0008



2000103757 AQUA757

Bent outlet

2030050434 ACXX2005

Bent outlet

2030050435 ACXX2006







Shower pipe

2030041525 ACXX2003

Hygiene unit for F5L single-lever wall mixers

2030039446 ACLM9001

Solenoid valve cartridge

2030045522 ACXX9002