


Modell-Linie: F5L | F5LT2020

Showers | Manual shower





KWC-No.

2030066509

F5L-Therm stainless-steel shower panel for wall mounting with single-lever thermostat DN 15 and connecting nozzle for shower head. For connection to hot and cold water. Function block with integrated mixing cartridge and pre-assembled hygiene unit including sensor with control electronics to perform automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass so lenoid-operated flush valve cartridge necessary) and storage of statistical data. Thermostaticallycontrolled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. All-metal construction, visible parts high-polished, chrome-plated. Connecting nozzles for separate required DN 15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Stainless steel housing with raised function surface and cover caps made of plastic. With adjustable and lockable connections with backflow preventer and strainers. Activated hygiene flushing, fixed interval of 24 hours. With option for parameterization and communication via optional, bidirectional remote control. Optional hygiene unit for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via plug-in power supply unit 6.75 V/12 V DC.

Housing dimensions 235 x 1160 x 90 mm (W x H x D)

Shower head and battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

| additional connections | |
|--------------------------------|--|
| with backflow preventer | |
| circulation | |
| compatible A3000 open | |
| connection with pay water disp | |
| default automatic hygiene flus | |
| with filter | |
| adjustable flow time | |
| functional principle | |
| for hand shower | |
| hygiene flushing | |
| diameter nominal | |
| inlet size | |
| Locking mechanism | |
| material casing | |
| material code casing | |
| material fitting | |
| minimum flow pressure | |
| type of mixing | |
| overall depth | |
| overall height | |

| no | |
|----------------------|---------------|
| yes | |
| no | |
| no | |
| not possible | |
| fixed interval 24 ho | urs |
| yes | |
| no | |
| manual | |
| no | |
| yes | |
| DN 15 | |
| G 1/2 A | |
| Top section, cerami | c |
| stainless steel | |
| 1.4301 Chrome Nic | kel steel V2A |
| brass-look | |
| 1 bar | |
| with thermostat | |
| 90 mm | |
| 1,160 mm | |





Modell-Linie: F5L | F5LT2020 Showers | Manual shower

| overall width | 235 mm | |
|-------------------------------|----------------------------|--|
| Parameterization | remote control | |
| power supply connection | 6,75 / 12 V DC | |
| position of power connection | from top / backside | |
| Type of power supply | Other | |
| protective system IP | IP59K | |
| with rosettes/cover plate | yes | |
| protective shutdown | no | |
| shower pipe draining | no | |
| Shower head | for separately shower head | |
| with shower set | no | |
| sound insulation | no | |
| surface finish casing | satin finished | |
| surface finish fitting | chromed | |
| surface treatment fitting | polished | |
| temperature limit | yes | |
| thermal disinfection | yes | |
| with transformer/power supply | no | |
| type of mounting | wall mounting | |
| type of operation | manual operation | |
| type of sensor | opto-electronic sensor | |
| type of shower | shower panel | |
| volume flow rate at 3 bar | 0.15 <i>V</i> s | |
| water connection | hose (gland nut) | |
| position of water connection | from top / backside | |
| with soap dish | no | |
| Accent colour | chrome-look (glossy) | |
| Basic colour | stainless steel-look | |

Mandatory Accessories



AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011



AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011

Battery compartment

3600002063 ACEX9023



Modell-Linie: F5L | F5LT2020 Showers | Manual shower





Power supply unit

2030039477 ACEX9001 Extension cable 5 m

ACEX9010

Optional Accessories



Flow controller 6.0 l/min

2030027586 ESHHE0004



Flow controller 12.0 l/min

2000104783 ESHHE0002 Solenoid valve cartridge

2030003033 EAQFU0001



Shower gel dish for F5 shower panels made of stainless steel

2030057077 ACXX2021



•

Housing extension for F5 shower panels made of stainless steel

2030057066 ACXX2011 Housing extension for F5 shower panels made of stainless steel

2030057067 ACXX2012 Housing extension for F5 shower panels made of stainless steel

2030057068 ACXX2013 Housing extension for F5 shower panels made of stainless steel

2030057069 ACXX2014



Modell-Linie: F5L | F5LT2020 Showers | Manual shower





2-button remote control for fittings F3 and F5

Housing extension for F5 shower panels made of stainless steel

2030057070 ACXX2015 **2030036849** ACEX9004



Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

Spare Parts





Stainless steel care set

2000109019 ZWSPL0024 Rosette

2030048765 ASET2006