


Modell-Linie: F5L | F5LT2022

Showers | Manual shower





KWC-No.

2030066541

F5L-Therm stainless-steel shower panel for wall mounting with single-lever thermostat DN 15 and connecting nozzle for shower head. For connection to hot and cold water. Function block with integrated mixing cartridge and mechanism for an optional water hygiene unit for automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and tumproof temperature stop, and ceramic disc technology. All-metal


construction, visible parts high-polished, chrome-plated. Connecting nozzles for separate required DN 15 KWC shower head with prefitted flow regulator 9.0 l/min. Stainless steel housing with raised function surface and cover caps made of plastic. With adjustable and lockable connections with backflow preventer and strainers.

Housing dimensions $235 \times 1160 \times 90 \text{ mm}$ (W x H x D)

Shower head must be ordered separately.

Technical Data

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
minimum flow pressure	
type of mixing	
overall depth	
overall height	
overall width	
with rosettes/cover plate	







Modell-Linie: F5L | F5LT2022 Showers | Manual shower

protective shutdown	no	
shower pipe draining	no	
Shower head	for separately shower head	
with shower set	no	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	yes	
type of mounting	wall mounting	
type of operation	manual operation	
type of shower	shower panel	
volume flow rate at 3 bar	0.15 l/s	
water connection	hose (gland nut)	
position of water connection	from top / backside	
with soap dish	no	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel	

Mandatory Accessories







AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011

Optional Accessories











Modell-Linie: F5L | F5LT2022 Showers | Manual shower

Flow controller 6.0 I/min

2030027586 ESHHE0004 Flow controller 12.0 I/min

2000104783 ESHHE0002 Hygiene unit for F5L single lever mixer shower panel

2030057065 ACLM2003 Shower gel dish for F5 shower panels made of stainless steel

2030057077 ACXX2021










Housing extension for F5 shower panels made of stainless steel

2030057066 ACXX2011 Housing extension for F5 shower panels made of stainless steel

2030057067 ACXX2012 Housing extension for F5 shower panels made of stainless steel

2030057068 ACXX2013 Housing extension for F5 shower panels made of stainless steel

2030057069 ACXX2014



Housing extension for F5 shower panels made of stainless steel

2030057070 ACXX2015

Spare Parts









Modell-Linie: F5L | F5LT2022 Showers | Manual shower

Flow controller 9,0 I/min	Rosette	Stainless steel care set
2000104782	2030048765	2000109019
ESHHE0001	ASET2006	ZWSPL0024