


### Modell-Linie: F5E | F5ET2031

Showers | Electronic self closing shower





### KWC-No.

### 2030067151


F5E-Therm thermostatic mixer DN 15 as finished installation kit for wall mounting in mounting material, for shower facilities. Electrically controlled, connects to hot water and cold water. Function block with integrated solenoid valve cartridge, thermostat and mechanism for two optional bypass solenoid valve cartridges for separate rinsing of the cold-water line and implementation of program-controlled thermal disinfection as well as for separate sampling of cold or hot water. Thermostat with metal handle with adjustable and tumproof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts high-polished, chrome-plated. With holding frame and profile seal, staniless-steel cover plate 190 x 245 mm with covered screw fixing including sensor with control electronics, rosette, backflow preventers and strainers. Depth adjustability 25 mm. Activated hygiene flushing 24 hours after last activation and storage of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Optionally for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

#### Technical Data

additional connections	no
with backflow preventer	yes
Built-in fitting model	Finishing section
calculation flow rate cold wat	0.15 l/s
calculation flow rate hot wate	0.15 l/s
circulation	no
compatible A3000 open	yes
connection with pay water disp	via electronic module
Cover plate height	245 mm
Cover plate width	190 mm
default automatic hygiene flus	24h after the last activity
default flow time	30 Seconds
with filter	yes
adjustable flow time	yes
functional principle	electronic self-closing
for hand shower	no
hygiene flushing	yes
diameter nominal	DN 15
inlet size	G 3/4 B
Locking mechanism	Top section, non-ceramic
material casing	stainless steel





### Modell-Linie: F5E | F5ET2031

Showers | Electronic self closing shower


material fitting	brass-look
maximum flow time	255 Seconds
minimum flow pressure	1 bar
minimum flow time	1 Seconds
type of mixing	with thermostat
Parameterization	remote control
power supply connection	6,75/12 V DC/A3000 open
position of power connection	from top
power consumption	1.5 Voltampere
Type of power supply	Transformer
with rosettes/cover plate	yes
protective shutdown	yes
shower pipe draining	no
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	in-wall installation with box
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of shower	in-wall fitting
Volume flow rate bypass PWH	0.05 l/s
volume flow rate at 3 bar	0.23 l/s
water connection	threaded connection (external)
position of water connection	from side
Accent colour	chrome-look (glossy)
Basic colour	stainless steel-look

### **Mandatory Accessories**









R5 System box for in-wall mixer

Battery compartment

**2030028990** F5BX2001 **3600002063** ACEX9023 Power supply unit

**2030039477** ACEX9001 Extension cable 5 m

**2030043814** ACEX9010




Modell-Linie: F5E | F5ET2031 Showers | Electronic self closing shower

#### **Optional Accessories**







Extension set

2030067889

ACXT9001


Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005



2-button remote control for fittings F3 and F5

**2030036849** ACEX9004



Set for flushing the cold-water line

**2030071564** ACXT2005

Electronic module EM5 for F5 shower

2030041918 ACET2001

**Spare Parts** 

Cover

2030003258 EAQLT0002





## Temperature handle

**2030047082** ASXT9003



Temperature stop

2030003296 EAQLT0003



Solenoid valve cartridge

2030003033 EAQFU0001

2030003033 EAQFU0001

taps

KWC Group AG | Home: info@kwc.com| Professional: kwc-export.int@kwc.com | www.kwc.com



Modell-Linie: F5E | F5ET2031 Showers | Electronic self closing shower





Holding frame

**2030045472** ASXX9004 Stainless steel care set

2000109019 ZWSPL0024 Cleaning product CHROMOL

**2000105091** ZWSPL0023