


KWC

F5S-Therm self-closing thermostatic in-wall mixer

Modell-Linie: F5S | F5ST2036

Showers | Self closing showers





KWC-No. shower pipe draining thermal disinfection 2030067154 no yes 2030067163 yes yes With automatic shower pipe emptying 2030067158 no no Version without option for automatic water hygiene flushing or thermal disinfection 2030067167 yes no with automatic shower pipe draining

F5S-Therm self-closing thermostatic mixer DN 15 as finished installation kit for wall mounting in mounting kit, for shower facilities. Hydraulically controlled, connects to hot water and cold water. Function block with integrated FRAMIC self-closing cartridge, thermostat and mechanism for an optional water hygiene unit for automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. Additional mechanism for second bypass solenoid valve cartridge for separate rinsing of the cold-water line and separate sampling of cold or hot water. FRAMIC self-closing cartridge, low maintenance and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to medium-independent design. Continuously adjustable flow duration. Thermostat with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts high-polished, chrome-plated. Holding frame including profile seal, stainless steel cover 190 x 245 mm with covered screw fixing, chrome-plated plastic rosettes, non-return valve and strainers. Depth adjustability 25 mm. Version with automatic shower pipe emptying.

Technical Data

additional connections	no	
with backflow preventer	yes	
Built-in fitting model	Finishing section	
calculation flow rate cold wat	0.15 l/s	
calculation flow rate hot wate	0.15 l/s	
circulation	no	
compatible A3000 open	no	
connection with pay water disp	not possible	
with filter	yes	
adjustable flow time	yes	
functional principle	hydraulic self-closing	
for hand shower	no	
hygiene flushing	prepared	
diameter nominal	DN 15	
inlet size	G 3/4 B	
Locking mechanism	Top section, ceramic	
material casing	stainless steel	

кwс

F5S-Therm self-closing thermostatic in-wall mixer

Modell-Linie: F5S | F5ST2036 Showers | Self closing showers

material fitting	brass	
maximum flow time	35 Seconds	
minimum flow pressure	1 bar	
minimum flow time	5 Seconds	
type of mixing	with thermostat	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	yes	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	yes	
type of mounting	in-wall installation with box	
type of operation	manual operation	
type of shower	in-wall fitting	
volume flow rate at 3 bar	0.2 l/s	
water connection	threaded connection (external)	
position of water connection	from side	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel	

Mandatory Accessories



R5 System box for in-wall mixer

2030028990 F5BX2001


Optional Accessories




кwс

F5S-Therm self-closing thermostatic in-wall mixer

Modell-Linie: F5S | F5ST2036 Showers | Self closing showers





Extension set	Set for flushing the cold-water line	
2030067889	2030071564	
ACXT9001	ACXT2005	

Spare Parts





Cover

2030003258 EAQLT0002





Temperature handle

2030047082 ASXT9003

Push cap

2030049943 ASST2001

2030003296 EAQLT0003

Temperature stop



Rosette

2030048765 ASET2006



Plug chromed

2030053006 ASSX9004



FRAMIC Self-closing cartridge


2030046145 ASSX9001



Safety ring

2030048357

ASSX9003





кwс

F5S-Therm self-closing thermostatic in-wall mixer

Modell-Linie: F5S | F5ST2036 Showers | Self closing showers









Holding frame

2030045472 ASXX9004

Cover plate stainless steel

2030050138 ASST2004

Stainless steel care set

2000109019 ZWSPL0024

Cleaning product CHROMOL

2000105091 ZWSPL0023