


F5S-Therm self-closing thermostatic in-wall mixer

## Modell-Linie: F5S | F5ST2036

Showers | Self closing showers





## KWC-No.

#### 2030067154

#### 2030067163

With automatic shower pipe emptying

#### 2030067158

Version without option for automatic water hygiene flushing or thermal disinfection

#### 2030067167

with automatic shower pipe draining

F5S-Therm self-closing thermostatic mixer DN 15 as finished installation kit for wall mounting in mounting kit, for shower facilities. Hydraulically controlled, connects to hot water and cold water. Function block with integrated FRAMIC self-closing cartridge, thermostat and mechanism for an optional water hygiene unit for automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. Additional mechanism for second bypass solenoid valve cartridge for separate rinsing of the cold-water line and separate sampling of cold or hot water. FRAMIC self-closing cartridge, low maintenance

## shower pipe draining thermal disinfection

no	yes
yes	yes
no	no
yes	no

and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to medium-independent design. Continuously adjustable flow duration. Thermostat with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts high-polished, chrome-plated. Holding frame including profile seal, stainless steel cover 190 x 245 mm with covered screw fixing, chrome-plated plastic rosettes, non-return valve and strainers. Depth adjustability 25 mm. Version with automatic shower pipe emptying.

# Technical Data

additional connections	no
with backflow preventer	yes
Built-in fitting model	Finishing section
calculation flow rate cold wat	0.15 Vs
calculation flow rate hot wate	0.15 l/s
circulation	no
compatible A3000 open	no
connection with pay water disp	not possible
with filter	yes
adjustable flow time	yes
functional principle	hydraulic self-closing
for hand shower	no
hygiene flushing	prepared
diameter nominal	DN 15
inlet size	G 3/4 B
Locking mechanism	Top section, ceramic
material casing	stainless steel



 ${\it F5S-Therm self-closing\ thermostatic\ in-wall\ mixer}$ 

**Modell-Linie: F5S | F5ST2036** Showers | Self closing showers

material fitting	brass
maximum flow time	35 Seconds
minimum flow pressure	1 bar
minimum flow time	5 Seconds
type of mixing	with thermostat
with rosettes/cover plate	yes
protective shutdown	no
shower pipe draining	yes
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
type of mounting	in-wall installation with box
type of operation	manual operation
type of shower	in-wall fitting
volume flow rate at 3 bar	0.2 l/s
water connection	threaded connection (external)
position of water connection	from side
Accent colour	chrome-look (glossy)
Basic colour	stainless steel

# **Mandatory Accessories**



# R5 System box for in-wall mixer


**2030028990** F5BX2001

# **Optional Accessories**



F5S-Therm self-closing thermostatic in-wall mixer

# Modell-Linie: F5S | F5ST2036 Showers | Self closing showers





#### Extension set

# 2030067889

ACXT9001

#### Set for flushing the cold-water line

2030071564 ACXT2005

# **Spare Parts**









Temperature handle

**2030047082** ASXT9003

Temperature stop

**2030003296** EAQLT0003

Plug chromed

**2030053006** ASSX9004

Push cap

**2030049943** ASST2001







FRAMIC Self-closing cartridge



# Safety ring

2030048357

ASSX9003

Rosette

2030048765 ASET2006

2030046145 ASSX9001

Stainless steel care set

2000109019 ZWSPL0024



F5S-Therm self-closing thermostatic in-wall mixer

Modell-Linie: F5S | F5ST2036 Showers | Self closing showers



Cleaning product CHROMOL

**2000105091** ZWSPL0023