


F3E-Therm electronic thermostat mixer

Modell-Linie: F3E | F3ET2004

Showers | Electronic self closing shower





KWC-No.

2030067170

F3E-Therm thermostatic mixer DN 15 as finished installation kit for wall mounting in mounting material, for shower facilities. Electrically controlled, connects to hot water and cold water. Function block with integrated solenoid valve cartridge and thermostat, with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts high-polished, chrome-plated. With holding frame and profile seal, stainless-steel cover plate 190×245 mm with covered screw fixing including sensor with control electronics, rosette, backflow preventers and strainers. Depth adjustability 25 mm. Activated

hygiene flushing 24 hours after last activation and storage of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Either for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via power supply unit 6.75 V/12 V DC.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

additional connections	
with backflow preventer	
Built-in fitting model	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
default flow time	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material fitting	
maximum flow time	
minimum flow pressure	

no	
yes	
Finishing section	
0.15 l/s	
0.15 l/s	
no	
no	
not possible	
24h after the last activity	/
30 Seconds	
yes	
yes	
electronic self-closing	
no	
yes	
DN 15	
G 3/4 B	
Top section, non-ceramic	
stainless steel	
brass	
255 Seconds	
1 bar	











F3E-Therm electronic thermostat mixer

Modell-Linie: F3E | F3ET2004

Showers | Electronic self closing shower


minimum flow time	1 Seconds
type of mixing	with thermostat
Parameterization	remote control
power supply connection	6,75/12 V DC
position of power connection	from top
power consumption	1.5 Voltampere
Type of power supply	Transformer
with rosettes/cover plate	yes
protective shutdown	yes
shower pipe draining	no
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	manual thermal disinfection
with transformer/power supply	no
type of mounting	in-wall installation with box
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of shower	in-wall fitting
volume flow rate at 3 bar	0.23 l/s
water connection	threaded connection (external)
position of water connection	from side
Accent colour	chrome-look (glossy)
Basic colour	stainless steel

Mandatory Accessories









R3 system box for in-wall mixers

2030036141 F3BX2001 R5 System box for in-wall mixer

2030028990 F5BX2001 Power supply unit

2030039477 ACEX9001 Extension cable 5 m

2030043814 ACEX9010


Optional Accessories



F3E-Therm electronic thermostat mixer

Modell-Linie: F3E | F3ET2004

Showers | Electronic self closing shower







Extension set

2030067889 ACXT9001 Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005 2-button remote control for fittings F3 and F5

2030036849 ACEX9004

Spare Parts









Cover

2030048769 ASET2005

Temperature handle

2030048766 ASET2004 Temperature stop

2030003296


Solenoid valve cartridge

2030003033









Holding frame

2030045472 ASXX9004 Sensor, ID 12/00001

2030048628 ASEX2001 Cover plate stainless steel

2030048775 ASET2007

Extension set

2030067889 ACXT9001



F3E-Therm electronic thermostat mixer

Modell-Linie: F3E | F3ET2004 Showers | Electronic self closing shower





Cleaning product CHROMOL

2000105091 ZWSPL0023

Stainless steel care set

2000109019 ZWSPL0024