


KWC F5

Smart Urinal sensor

Modell-Linie: F5E | F5EF3008

Flushing systems | Electronic urinal flushing systems





KWC-No.

2030067530

White plastic housing

2030067531

Black plastic housing

F5 smart urinal sensor for overhead installation for central flushing of urinal systems in a room. Control module designed with white plastic housing, for multiple simultaneous user detection and touch-free triggering of flushing programmes for connected F5 smart urinal units via wireless communication. Option to connect up to 20 F5 smart urinal units. The area covered by the sensors is dependent on the ceiling height. Activated, washing area-dependent hygiene flushing 24 hours after last activation and saving of statistical data. Commissioning and flushing programme selection and

Basic colour

white

black

parametrisation for each smart urinal unit via the necessary app, installed on Bluetooth®-enabled mobile devices from Android 7 or iOS 11.

Connection voltage 110–240 V AC, 50/60 Hz Protection class IP20 Area covered 5 x 2.5 m at ceiling height 3 m Housing dimensions 160×35 mm (D x H)

Technical Data

Para	amet	eriza	ation

type of mounting

Basic colour

арр

ceiling mounting

white





Mandatory Accessories







F5 smart urinal unit for single ceramic urinals

2030067532 ACEF3002 F5 smart urinal unit for single urinal made of stainless steel

2030070859 ACEF3003 F5 smart urinal unit for series of urinals made of stainless steel

2030072412 ACEF3004