


KWC F5E - A3000 open Electronic washbasin tap for in-wall installation

Modell-Linie: F5E | F5EV1017
Taps | Electronic taps



KWC-No.

2030067880

NEW

F5E - A3000 open washbasin tap DN 15 as finished installation kit for in-wall installation in the basic installation kit, for sanitary facilities. Especially suitable for facilities at risk of vandalism. Electronically controlled, for connection to pre-mixed hot water or cold water. With waterproof electronic module and electric T-junction for connection to system cable, solenoid valve, stainless steel cover plate 190 x 245 x 2 mm, mounting from the front with safety screws, including piezo push-button with start/stop function

and recess for KWC wall outlet DN 15 (required separately). Depth adjustability 20 mm. Activated hygiene flushing 24 hours after the last activity. With facility for parameterization, cleaning deactivation and communication via ECC2 function controller, 24 V DC.

Wall outlet must be ordered separately.

Technical Data

Built-in fitting model
compatible A3000 open
Cover plate height
Cover plate width
default automatic hygiene flush
default flow time
depressurised
with filter
adjustable flow time
functional principle
hygiene flushing
diameter nominal
Locking mechanism
material code casing
material fitting
maximum flow time
minimum flow pressure
minimum flow time
type of mixing
Parameterization
power supply connection
position of power connection
Type of power supply

Finishing section
yes
245 mm
190 mm
24h after the last activity
10 Seconds
no
yes
yes
electronic self-closing
yes
DN 15
Top section, non-ceramic
1.4301 Chrome Nickel steel V2A
brass-look
6,500 Seconds
1 bar
1 Seconds
no
network
A3000 open 24 VDC
from top
Transformer



KWC F5E - A3000 open Electronic washbasin tap for in-wall installation

Modell-Linie: F5E | F5EV1017
Taps | Electronic taps

protective system IP	IP59K
protective shutdown	yes
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
with transformer/power supply	no
type of mounting	in-wall installation with box
type of operation	sensor operation
type of sensor	piezo-electronic sensor
type of tap	in-wall tap
volume flow rate at 3 bar	0.46 l/s

Mandatory Accessories



R3 system box for in-wall taps

2030036142
F3BV1001



Wall outlet for in-wall washbasin taps

2030071655
ACXX1008



Wall outlet for in-wall washbasin taps

2030071654
ACXX1009



Wall outlet for in-wall washbasin taps

2030071663
ACXX1010



ECC2 function controller

2000108123
ZA3OP0011



ECC2 function controller

2030016282
ZA3OP0022



System cable

2000100801
ZAQQA077




System cable

2000100852
ZAQQA078


KWC F5E - A3000 open Electronic washbasin tap for in-wall installation

Modell-Linie: F5E | F5EV1017
Taps | Electronic taps



System cable


2000104274
ZAQUA012



System cable


2000104272
ZAQUA011

Spare Parts



Solenoid valve

2000101328
ZAQUA032



Piezo Switch

2000104441
EAT300001



Electrical T junction

2000100853
ZAQUA075



Stainless steel care set

2000109019
ZWSPL0024



Cleaning product CHROMOL

2000105091
ZWSPL0023