


### **KWC** F3S

### Self-closing shower fitting for in-wall installation

Modell-Linie: F3S | F3SV2011 Showers | Self closing showers





#### KWC-No.

#### 2030068215

F3S self-closing straight-way valve DN 15 as finished installation kit for in-wall installation in basic installation kit, for shower facilities. Especially suitable for facilities at risk of vandalism. Self-closing functional part, hydraulically controlled, piston-free design, self-closing, continuously adjustable flow duration. For connection to pre-

mixed hot water or cold water. Housing including shuttle valve seat, pressure cap with safety screws, visible parts, polished chromium-plated brass. Stainless steel cover plate  $190\times245\times2$  mm, mounting from the front with safety screws and rosette. Depth adjustability 20 mm.

# NEW

### **Technical Data**

additional connections	
with backflow preventer	
Built-in fitting model	
circulation	
connection with pay water disp	
Cover plate height	
Cover plate width	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	
type of mixing	
with rosettes/cover plate	
protective shutdown	
shower pipe draining	
sound insulation	

no
no
Finishing section
no
not possible
245 mm
190 mm
yes
yes
hydraulic self-closing
no
no
DN 15
G 3/4 B
Top section, non-ceramic
stainless steel
brass-look
35 Seconds
1 bar
5 Seconds
no
yes
no
no
no
·





### **KWC** F3S

## Self-closing shower fitting for in-wall installation

Modell-Linie: F3S | F3SV2011 Showers | Self closing showers

surface finish casing	satin fir
surface finish fitting	chrome
surface treatment fitting	polishe
temperature limit	no
thermal disinfection	no
type of mounting	in-wall
type of operation	manua
type of shower	in-wall
volume flow rate at 3 bar	0.4 l/s
water connection	threade
Accent colour	chrome
Basic colour	stainles

satin finished	
chromed	
polished	
no	
no	
in-wall installation with box	
manual operation	
in-wall fitting	
0.4 l/s	
threaded connection (external)	
chrome-look (glossy)	
stainless steel-look	

#### **Optional Accessories**



#### Extension set

**2000101451** AQRM900