



Modell-Linie: F3S | F3SV2012

Showers | Self closing showers





KWC-No.

2030070435

F3S shower panel made of stainless steel for wall mounting with DN 15 self-closing straight-way valve and connecting nozzles for shower head. Especially suitable for facilities at risk of vandalism. Hydraulically controlled, for connection from the rear to pre-mixed hot or cold water. Self-closing functional part, piston-free design, self-closing and stepless adjustment of flow duration. Valve housing including shuttle valve seat, visible parts polished chromium-plated. Connecting nozzles for the required additional DN

15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Housing made of stainless steel, single-piece enclosed, including safety screws. Connecting hose with lockable water flow regulator and strainer.

Housing dimensions $232 \times 1160 \times 90$ mm (W x H x D)

Shower head must be ordered separately.

NEW

Technical Data

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
dia meter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	
type of mixing	
overall depth	
overall height	
overall width	

no	
yes	
no	
no	
not possible	
yes	
yes	
hydraulic self-closing	
no	
no	
DN 15	
G 1/2 A	
Top section, ceramic	
stainless steel	
1.4301 Chrome Nickel steel V2A	
brass-look	
35 Seconds	
1.5 bar	
5 Seconds	
no	
90 mm	
1,160 mm	
235 mm	





Modell-Linie: F3S | F3SV2012 Showers | Self closing showers

protective shutdown shower pipe draining Shower head with shower set sound insulation surface finish casing surface finish fitting surface treatment fitting	no no for separately shower head no no
Shower head with shower set sound insulation surface finish casing surface finish fitting	for separately shower head no no
with shower set sound insulation surface finish casing surface finish fitting	no no
sound insulation surface finish casing surface finish fitting	no
surface finish casing surface finish fitting	
surface finish fitting	
	satin finished
surface treatment fitting	chromed
	polished
temperature limit	no
thermal disinfection	no
type of mounting	wall mounting
type of operation	manual operation
type of shower	shower panel
volume flow rate at 3 bar	0.15 l/s
water connection	hose (gland nut)
position of water connection	from top / backside
with soap dish	no
Accent colour	
Basic colour	chrome-look (glossy)

Mandatory Accessories







AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011

Optional Accessories



Modell-Linie: F3S | F3SV2012 Showers | Self closing showers





Flow controller 6.0 l/min

Flow controller 12.0 l/min

2030027586 ESHHE0004 **2000104783** ESHHE0002

Spare Parts







Push cap

2030042960 ASSV2001



Flow controller 9,0 l/min

2000104782 ESHHE0001



Functional part

2000104352 ESHOW0001

O-Ring, red

2030042961 ASSV2002







Valve seat DN 15

2000104790 ESHOW0040

)

Push-on rosette

2000104892 EAQLN0008 Hexagonal socket wrench

2000106127 ZFITG0003



Modell-Linie: F3S | F3SV2012 Showers | Self closing showers





Stainless steel care set

2000109019 ZWSPL0024 Cleaning product CHROMOL

2000105091 ZWSPL0023