


KWC F5S-Mix

Self-closing wall-mounted mixer for rear panel mounting

Modell-Linie: F5S | F5SM1012

Taps | Self closing taps





KWC-No.

2030071618

Technical Data

F5S-Mix self-closing wall-mounted mixer DN 15 as single mixer with angled outlet, for sanitary facilities, for concealed mounting. Especially suitable for facilities at risk of vandalism. FRAMIC selfclosing mixer cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium separated design. Stepless adjustment of flow duration. With adjustable and turnproof temperature stop with backflow preventers and strainers. For connection to hot and cold water. All-metal construction, polished, chromium-plated brass. Anti-theft aerator with integrated flow regulator 6.0 //min. Connecting flange with overlapping wall bushings for wall thicknesses from 50 to 240 mm.

Other wall thicknesses on request.

| with backflow preventer | <u> </u> |
|--------------------------------|----------|
| calculation flow rate cold wat | |
| calculation flow rate hot wate | |
| depressurised | |
| with filter | |
| adjustable flow time | |
| functional principle | |
| hygiene flushing | |
| dia meter nominal | |
| inlet size | |
| Locking mechanism | |
| material fitting | |
| maximum flow time | |
| minimum flow pressure | |
| minimum flow time | |
| type of mixing | |
| with rosettes/cover plate | |
| protective shutdown | |
| sound insulation | |
| Spout | |
| spout projection | |
| surface finish fitting | |
| surface treatment fitting | |
| temperature limit | |

| yes | |
|------------------------|--|
| 0.07 l/s | |
| 0.07 l/s | |
| no | |
| yes | |
| yes | |
| hydraulic self-closing | |
| no | |
| DN 15 | |
| G 1/2 B | |
| Top section, ceramic | |
| brass-look | |
| 35 Seconds | |
| 1 bar | |
| 5 Seconds | |
| yes | |
| yes | |
| no | |
| no | |
| fixed | |
| 170 mm | |
| chromed | |
| polished | |
| yes | |





KWC F5S-Mix

Self-closing wall-mounted mixer for rear panel mounting

Modell-Linie: F5S | F5SM1012 Taps | Self closing taps

| thermal disinfection | no | |
|---------------------------|--------------------------------|--|
| type of mounting | concealed | |
| type of operation | manual operation | |
| type of tap | bib tap | |
| volume flow rate at 3 bar | 0.1 l/s | |
| water connection | threaded connection (external) | |
| Accent colour | none | |
| Basic colour | chrome-look (glossy) | |
| | | |

Optional Accessories



Outlet extension

2000101463 AQRM909

Spare Parts





Aerator

2000101160 ZAQUA087

Guide bushing

2030023924 ETAPS0040





Plug chromed

2030053006 ASSX9004



Handle push cap

2030050753 ASSM9004



KWC F5S-Mix

Self-closing wall-mounted mixer for rear panel mounting

Modell-Linie: F5S | F5SM1012 Taps | Self closing taps





Wall flange

2030058762 ACXM1002