


KWC F5E

WC flush valve for in-wall installation

Modell-Linie: F5E | F5EF4008

Flushing systems | Electronic WC flushing systems





KWC-No.

F5E electronic WC flush valve for in-wall installation

F5E WC flush valve DN 20 as finished installation kit for in-wall installation in basic installation kit, touch-free, opto-electronically controlled. With solenoid flush valve fitting group I including enclosed throttle insert to reduce the flush volume, holding frame with profile seal and stainless steel cover plate 190 x 245 mm with integrated sensor and covered screw fixing. Depth adjustability 20 mm. Parameterisation and communication possible via optional bidirectional remote control. Optionally for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable or AQUA 3000 open system accessories must be ordered separately.



Technical Data

Technical Data	
Built-in fitting model	
calculation flow rate cold wat	
Cover plate height	
Cover plate width	
default automatic hygiene flus	
Flushing volume adjustable	
functional principle	
hygiene flushing	
diameter nominal	
material casing	
material code casing	
material fitting	
maximum flow pressure	
maximum flushing flow	
maximum flush water volume	
minimum flow pressure	
minimum flushing flow	
minimum flush water volume	
Parameterization	
power supply connection	
position of power connection	
Type of power supply	
protective system IP	

Finishing section
1 l/s
245 mm
190 mm
24h after the last activity
yes
electronic self-closing
yes
DN 20
stainless steel
1.4301 Chrome Nickel steel V2A
brass-look
4 bar
1.3 <i>V</i> s
9 Liter
1.2 bar
1 l/s
6 Liter
remote control
6,75 / 12 V DC / A3000 open
from top
Battery/Mains power supply
IP59K









KWC F5E

WC flush valve for in-wall installation

Modell-Linie: F5E | F5EF4008

Flushing systems | Electronic WC flushing systems

protective shutdown	yes
sound insulation	no
surface finish	satin finished
surface finish casing	satin finished
with transformer/power supply	no
type of flushing fitting	WC flush valve
type of mounting	in-wall installation with box
type of operation	sensor operation
type of sensor	opto-electronic sensor
water connection	threaded connection (external)

Mandatory Accessories









R3 system box for WC flush valve

2030068205 F3BF4001

AQUAFIX installation frame with WC flush valve for in-wall installation


3600005980 AQFX0012

AQUAFIX installation frame for barrier-free WC systems, with WC flush valve for in-wall installation **3600005981** AQFX0013

Battery compartment

3600002063 ACEX9023







In-wall power supply

Power supply unit

2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

2030039825 ACEX9003

Optional Accessories



KWC F5E


WC flush valve for in-wall installation

Modell-Linie: F5E | F5EF4008 Flushing systems | Electronic WC flushing systems









Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

Extension cable

2000101055 ZAQUA073

Flushing pipe for in-wall installation

2000101466 AQRM920

Spare Parts









Remote operation hose

2000104803 EAQLN0019

2030045472 ASXX9004

Holding frame

Stainless steel care set

2000109019 ZWSPL0024

Cleaning product CHROMOL

2000105091 ZWSPL0023