


## KWC F7E Electronic pillar tap

Modell-Linie: F7 | F7EV1001 Taps | Electronic taps





#### KWC-No.

#### 3600001255

F7E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve and sensor in and strainer. Control electronics, solenoid valve and sensor in stainless steel housing, brushed surface, outlet height 115 mm and projection 125 mm. Angle-adjustable and anti-theft aerator with integrated flow regulator 5.7 l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional bidirectional remote control or C module with the necessary app. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting, for installation below the washbasin, or for separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

#### **Technical Data**

with backflow preventer
compatible A3000 open
default automatic hygiene flus
depressurised
with filter
functional principle
hygiene flushing
diameter nominal
inlet size
Locking mechanism
material fitting
minimum flow pressure
type of mixing
Parameterization
Pop-up waste set
power supply connection
position of power connection
Type of power supply
with rosettes/cover plate
protective shutdown
sound insulation
Spout
surface finish fitting
surace mismudig

no
yes
24h after the last activity
no
yes
electronic self-closing
yes
DN 15
G 3/8
Top section, non-ceramic
stainless steel
1 bar
no
remote control
no
6,75 / 12 V DC / A3000 open
from bottom
Other
no
yes
no
fixed
brushed













# KWC F7E

# Electronic pillar tap


Modell-Linie: F7 | F7EV1001 Taps | Electronic taps

surface treatment fitting	
temperature limit	
thermal disinfection	
with transformer/power supply	
type of mounting	
type of operation	
type of sensor	
type of tap	
water connection	
Accent colour	
Basic colour	

brushed			
no			
no			
no			
tap hole			
sensor operation			
opto-electronic sensor			
pillartap			
hose (gland nut)			
none	 •	•	
stainless steel			

#### **Mandatory Accessories**







#### Power supply unit

2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

In-wall power supply

2030039825

## **Optional Accessories**









Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005

2-button remote control for fittings F3

**2030036849** ACEX9004

C module

**3600001331** ACEX9020

PURETHERM under-table thermostat

**2030012758** PURE0031

#### **Spare Parts**



# KWC F7E Electronic pillar tap

Modell-Linie: F7 | F7EV1001 Taps | Electronic taps







Hose

**2030041311** ASXX1005

Stainless steel care set

**2000109019** ZWSPL0024

Cleaning product CHROMOL

**2000105091** ZWSPL0023