


# KWC F7E Electronic pillar tap

# Modell-Linie: F7 | F7EV1001 Taps | Electronic taps





### KWC-No.

### 3600001255

F7E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve and sensor in and strainer. Control electronics, solenoid valve and sensor in stainless steel housing, brushed surface, outlet height 115 mm and projection 125 mm. Angle-adjustable and anti-theft aerator with integrated flow regulator 5.7 l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional bidirectional remote control or C module with the necessary app. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting, for installation below the washbasin, or for separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

### **Technical Data**

with backflow preventer	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
Parameterization	
Pop-up waste set	
power supply connection	
position of power connection	
Type of power supply	
with rosettes/cover plate	
protective shutdown	
sound insulation	
Spout	
surface finish fitting	

no
yes
24h after the last activity
no
yes
electronic self-closing
yes
DN 15
G 3/8
Top section, non-ceramic
stainless steel
1 bar
no
remote control
no
6,75 / 12 V DC / A3000 open
from bottom
Other
no
yes
no
fixed
brushed













# **KWC** F7E Electronic pillar tap


Modell-Linie: F7 | F7EV1001 Taps | Electronic taps

surface treatment fitting
temperature limit
thermal disinfection
with transformer/power supply
type of mounting
type of operation
type of sensor
type of tap
water connection
Accent colour
Basic colour

no			
no			
no			
tap hole			
sensor operation			
opto-electronic sensor			
pillartap			
hose (gland nut)			
none			

# **Mandatory Accessories**







# Power supply unit

**2030039477** ACEX9001 Extension cable 5 m

**2030043814** ACEX9010 In-wall power supply

2030039825

# **Optional Accessories**







Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005 2-button remote control for fittings F3 and F5

**2030036849** ACEX9004 PURETHERM under-table thermostat

**2030012758** PURE0031

# **Spare Parts**



# KWC F7E Electronic pillar tap

Modell-Linie: F7 | F7EV1001 Taps | Electronic taps





Stainless steel care set

**2000109019** ZWSPL0024

Cleaning product CHROMOL

**2000105091** ZWSPL0023