


KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer with pre-fitted hygiene unit

Modell-Linie: F5L | F5LT1112

Taps | Manual taps



KWC-No.

360003807

Projection 195 mm

360003809

Projection 135 mm

360003852

Projection 255 mm

spout projection

100 mm

40 mm

160 mm

NEW

F5L-Therm thermostatic single-lever mixer DN 15 as wall-mounted mixer for wall mounting with lockable swivelling spout, for sanitary facilities. Thermostatically controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop and ceramic disc technology. Pre-fitted hygiene unit with C-module including control electronics, 6 V lithium battery (CR-P2) and solenoid valve cartridge for automatic hygiene flushing and saving of statistical data. For connection to hot and cold water. Scald-protected, safe-touch housing, all-metal construction, polished chromium-plated brass. Volume-reduced, smooth water lines made of brass without nickel coating, decoupled

from the tap housing. With thermal insulation components to reduce heat transfer from the tap housing to the cold-water line. Laminar jet controller with integrated flow rate controller 6.0 l/min. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. Reach 135 mm. Activated hygiene flushing, fixed interval of 24 hours. With option for radio-controlled parameterisation, read-out of statistical data, realisation of predefined calendar functions as well as grouping of taps to perform predefined control functions via the necessary app.

Technical Data

depressurised

adjustable flow time

functional principle

diameter nominal

inlet size

Locking mechanism

material fitting

type of mixing

Pop-up waste set

protective shutdown

sound insulation

Spout

spout projection

surface finish casing

surface finish fitting

surface treatment fitting

temperature limit

with transformer/power supply

type of mounting

no

no

manual

DN 15

G 1/2 B

Top section, ceramic

brass-look

with thermostat

no

no

no

rotating, bottom

40 mm

chromed


chromed

polished

yes

no

wall mounting



KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer with pre-fitted hygiene unit

Modell-Linie: F5L | F5LT1112

Taps | Manual taps

type of operation

manual operation

type of tap

bib tap

water connection

S-connections

Accent colour

none

Basic colour

chrome-look (glossy)

Optional Accessories



Theft-proof housing for aerator

2000104778

ZTAPS0005