


Shower panel made of stainless steel with diverter between overhead shower and hand shower

Modell-Linie: F5 | F5ST2046

Showers | Self closing showers





KWC-No.

3600004618

F5S-Therm shower panel made of stainless steel for wall mounting with DN 15 self-closing thermostatic mixer and diverter between overhead shower and hand shower. Hydraulically controlled, connects to hot water and cold water. Function block with integrated FRAMIC self-closing cartridge, thermostat and preassembled hygiene unit including sensor with control electronics to perform automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. FRAMIC self-closing cartridge, low maintenance and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to medium-independent design. Flow duration can be adjusted by any increment. Thermostat with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts polished chromeplated. Connecting nozzles for separately required DN 15 KWC shower head with pre-fitted flow regulator 9.0 l/min. Stainless steel

housing with raised function surface and cover caps made of plastic. Hand shower connection on the left and chrome-plated plastic hand shower holder on the right, both pre-assembled on the side. Connector hoses with lockable water flow control with backflow preventer and strainer. Activated hygiene flushing, fixed interval of 24 hours. With option for parameterization and communication via optional, bidirectional remote control. Optional hygiene unit for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via plug-in power supply unit 6.75 V/12 V DC.

Housing dimensions 235 x 1160 x 90 mm (W x H x D)

Shower head, hand shower with shower hose and battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

recimical bata	
additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
maximum flow time	

for handshower with switch
yes
no
no
not possible
fixed interval 24 hours
yes
yes
nydraulic self-closing
yes
yes
DN 15
G 1/2 A
Top section, ceramic
stainless steel
1.4301 Chrome Nickel steel V2A
orass-look
35 Seconds















Shower panel made of stainless steel with diverter between overhead shower and hand shower

Modell-Linie: F5 | F5ST2046 Showers | Self closing showers

minimum flow pressure	1.5 bar
minimum flow time	5 Seconds
type of mixing	with thermostat
overall depth	90 mm
overall height	1,160 mm
overall width	235 mm
Parameterization	remote control
power supply connection	6,75/12 V DC
position of power connection	from top / backside
Type of power supply	other
protective system IP	IP59K
with rosettes/cover plate	yes
protective shutdown	no
shower pipe draining	no
Shower head	for separately shower head
with shower set	no
sound insulation	no
surface finish casing	satin finished
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	wall mounting
type of operation	manual operation
type of sensor	opto-electronic sensor
type of shower	shower panel
volume flow rate at 3 bar	0.15 l/s
water connection	hose (gland nut)
position of water connection	from top / backside
with soap dish	no
Accent colour	chrome-look (glossy)
Basic colour	stainless steel-look

Mandatory Accessories









AQUAJET-Slimline shower head for KWC shower panels and systems

AQUAJET-Comfort shower head for KWC shower panels and systems

MÜNCHEN shower head for KWC shower panels and systems

Battery compartment




Shower panel made of stainless steel with diverter between overhead shower and hand shower

Modell-Linie: F5 | F5ST2046

Showers | Self closing showers

2030054255 SHAS0011 **2030054254** SHAC0011 **2030054793** SHMU0011 **3600002063** ACEX9023





Power supply unit

2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

Optional Accessories









Flow controller 6.0 I/min

2030027586 ESHHE0004 Flow controller 12.0 l/min

2000104783 ESHHE0002 Hand shower

2030051216 ACXX2007 Shower bracket

2030051217 ACXX2008









Set for thermal disinfection

2030057940 ACXT2001 Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005 2-button remote control for fittings F3 and F5

2030036849 ACEX9004 Housing extension for F5 shower panels made of stainless steel

2030057066 ACXX2011




Shower panel made of stainless steel with diverter between overhead shower and hand shower


Modell-Linie: F5 | F5ST2046

Showers | Self closing showers









Housing extension for F5 shower panels made of stainless steel

2030057067 ACXX2012

Housing extension for F5 shower panels made of stainless steel

2030057068 ACXX2013


Housing extension for F5 shower panels made of stainless steel

2030057069 ACXX2014

Housing extension for F5 shower panels made of stainless steel

2030057070 ACXX2015





Shower gel dish for F5 shower panels made of stainless steel

2030057077

ACXX2021

Connection set for shower panel

2000104916 ZSHOW0006

Spare Parts









Flow controller 9,0 I/min

2000104782 ESHHE0001

Cover

2030031443 ESHOW0059

Temperature handle

2030047082 ASXT9003

Temperature stop

2030003296 EAQLT0003



Shower panel made of stainless steel with diverter between overhead shower and hand shower

Modell-Linie: F5 | F5ST2046 Showers | Self closing showers









Thermocouple





Push cap

2030049943 ASST2001



Guide ring

2030048356 ASSX9002



Safety ring

2030048765 ASET2006

Rosette



Plug chromed



FRAMIC Self-closing cartridge

2030046145 ASSX9001

Solenoid valve cartridge

2030003033 EAQFU0001





Stainless steel care set

2000109019 ZWSPL0024



2000105091 ZWSPL0023