


KWC F5LME Hybrid washbasin tap

Modell-Linie: F5L | F5LME005

Taps | Manual taps





KWC-No.

3600008404

F5LME hybrid washbasin tap DN 15 as pillar mixer with swivelling spout, can be locked in the centre position. Adjustable swivel ranges of 50°, 120° and 360°. For connection to hot water and cold water via hoses with strainers. Single lever mixer with mixer cartridge with ceramic disc technology and adjustable, turn-proof temperature stop. Alternative activation using hand reflection via an opto-electronic sensor for time-controlled water release with preset mixing water temperature. Mixer cartridge, solenoid valve and sensor with control electronics in all-metal housing, brushed stainless steel. Laminar jet controller with integrated flow rate controller (8.0 l/min). Projection 220 mm. Activated water hygiene

flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting for installation under the kitchen sink or for separate power supply via $6.75\ \text{V}/12\ \text{V}\ \text{DC}$ power supply unit or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

NEW

Technical Data

recillical Data	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
Pop-up waste set	
with rosettes/cover plate	
Spout	
spout projection	
surface finish fitting	
temperature limit	
thermal disinfection	
type of mounting	
type of operation	
type of tap	
volume flow rate at 3 bar	
water connection	
Accent colour	

no
yes
manual
prepared
DN 15
Top section, non-ceramic
stainless steel
1 bar
yes
no
no
rotating, top
175 mm
brushed
yes
yes
tap hole
manual operation
pillartap
0.13 l/s
hose (gland nut)
none












KWC F5LME Hybrid washbasin tap

Modell-Linie: F5L | F5LME005 Taps | Manual taps

Mandatory Accessories









Battery compartment

3600002063 ACEX9023



2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

Plug-in power supply unit

3600002062



In-wall power supply

2030039825 ACEX9003

Optional Accessories







Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

PURETHERM under-table thermostat

2030012758



KWC F5LME Hybrid washbasin tap

Modell-Linie: F5L | F5LME005 Taps | Manual taps

Spare Parts





Solenoid valve cartridge

2030045522 ACXX9002

Backflow preventer DN 6

2030045816 ASXX9002