


KWC F5LME Hybrid washbasin tap

Modell-Linie: F5L | F5LME005
Taps | Manual taps



KWC-No.

3600008404

F5LME hybrid washbasin tap DN 15 as pillar mixer with swivelling spout, can be locked in the centre position. Adjustable swivel ranges of 50°, 120° and 360°. For connection to hot water and cold water via hoses with strainers. Single lever mixer with mixer cartridge with ceramic disc technology and adjustable, turn-proof temperature stop. Alternative activation using hand reflection via an opto-electronic sensor for time-controlled water release with preset mixing water temperature. Mixer cartridge, solenoid valve and sensor with control electronics in all-metal housing, brushed stainless steel. Laminar jet controller with integrated flow rate controller (8.0 l/min). Projection 220 mm. Activated water hygiene

flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting for installation under the kitchen sink or for separate power supply via 6.75 V/12 V DC power supply unit or AQUA 3000 open system accessories.


Battery compartment including battery or power supply unit with extension cable must be ordered separately.

NEW

Technical Data

depressurised
with filter
functional principle
hygiene flushing
diameter nominal
Locking mechanism
material fitting
minimum flow pressure
type of mixing
Pop-up waste set
with rosettes/cover plate
Spout
spout projection
surface finish fitting
temperature limit
thermal disinfection
type of mounting
type of operation
type of tap
volume flow rate at 3 bar
water connection
Accent colour


no
yes
manual
prepared
DN 15
Top section, non-ceramic
stainless steel
1 bar
yes
no
no
rotating, top
175 mm
brushed
yes
yes
tap hole
manual operation
pillar tap
0.13 l/s
hose (gland nut)
none



KWC F5LME Hybrid washbasin tap


Modell-Linie: F5L | F5LME005
Taps | Manual taps

Mandatory Accessories



Power supply unit

2030039477
ACEX9001



Extension cable 5 m

2030043814
ACEX9010



In-wall power supply

2030039825
ACEX9003

Optional Accessories



Bidirectional remote control for
electronic fittings F3 and F5

2030036654
ACEX9005



2-button remote control for fittings F3
and F5


2030036849
ACEX9004



PURETHERM under-table thermostat

2030012758
PURE0031

Spare Parts



Solenoid valve cartridge

2030045522



Backflow preventer DN 6

2030045816



KWC F5LME
Hybrid washbasin tap

Modell-Linie: F5L | F5LME005
Taps | Manual taps

ACXX9002

ASXX9002
