


## **KWC** F5LME Hybrid washbasin tap

### Modell-Linie: F5L | F5LME005

Taps | Manual taps





### KWC-No.

#### 3600008404

F5LME hybrid washbasin tap DN 15 as pillar mixer with swivelling spout, can be locked in the centre position. Adjustable swivel ranges of 50°, 120° and 360°. For connection to hot water and cold water via hoses with strainers. Single lever mixer with mixer cartridge with ceramic disc technology and adjustable, turn-proof temperature stop. Alternative activation using hand reflection via an opto-electronic sensor for time-controlled water release with preset mixing water temperature. Mixer cartridge, solenoid valve and sensor with control electronics in all-metal housing, brushed stainless steel. Laminar jet controller with integrated flow rate controller (8.0 l/min). Projection 220 mm. Activated water hygiene

flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting for installation under the kitchen sink or for separate power supply via  $6.75\,\text{V}/12\,\text{V}$  DC power supply unit or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

# NEW

### **Technical Data**

Technical Data	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
Locking mechanism	
material fitting	
minimum flow pressure	<u>-</u>
type of mixing	
Pop-up waste set	
with rosettes/cover plate	
Spout	
spout projection	
surface finish fitting	
temperature limit	
thermal disinfection	
type of mounting	<u>-</u>
type of operation	
type of tap	
volume flow rate at 3 bar	
water connection	
Accent colour	

no
yes
manual
prepared
DN 15
Top section, non-ceramic
stainless steel
1 bar
yes
no
no
rotating, top
175 mm
brushed
yes
yes
tap hole
manual operation
pillartap
0.13 <i>l/</i> s
hose (gland nut)
none












# **KWC** F5LME Hybrid washbasin tap

Modell-Linie: F5L | F5LME005

Taps | Manual taps

### **Mandatory Accessories**







Power supply unit

**2030039477** ACEX9001

Extension cable 5 m

**2030043814** ACEX9010

In-wall power supply

2030039825

### **Optional Accessories**







Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

**2030036849** ACEX9004

#### PURETHERM under-table thermostat

**2030012758** PURE0031

### **Spare Parts**



Solenoid valve cartridge

2030045522



# **KWC** F5LME Hybrid washbasin tap

**Modell-Linie: F5L | F5LME005** Taps | Manual taps

ACXX9002		